EPSON

Epson TM-H6000V-204P0 180 x 180 DPI Wired & Wireless Thermal POS printer

Brand : Epson

Product name : TM-H6000V-204P0

Product code: C31CG62204P0

- Integrated point-of-sale printer: Capable of receipt printing, slip printing and cheque processing
- Boost efficiency: Fast prints speeds up to 350mm/s[1], cheque processing and auto-cutter
- Flexible connectivity: Built-in USB and Ethernet in all models
- An investment for the future: ePOS-Print, ePOS-display and NFC
- Great value: Low total cost of ownership

350 mm/sec, 5.70 lps, 45 cps / 60 cps, 180 x 180 DPI, 79.50 ± 0.50 (W) mm x dia 83.00 mm, 24 V, 55 dB (A), 186 x 278 x 181 mm, 4400g
Epson TM-H6000V-204P0. Print technology: Thermal, Type: POS printer, Maximum resolution: 180 x 180 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 68 - 230 mm. Connectivity technology: Wired & Wireless, USB connector: USB Type-A / USB Type-B, Standard interfaces: Ethernet, NFC, USB, USB 1.1, USB 2.0. Sound pressure level (printing): 55 dB, Autocutter durability: 3 million cuts, Print head life: 200 km. Product colour: Black

Printing

Maximum resolution	180 x 180 DPI
Print speed	5.7 lps
Print speed	350 mm/sec
Character size	1.41 x 3.39 mm
Character density	17.8 cpi
Character sets	ANK
Print technology *	Thermal
Type *	POS printer

Paper handling

Maximum roll diameter	8.3 cm
Supported paper width	68 - 230 mm

Ports & interfaces

USB port *	✔
USB connector	USB Type-A / USB Type-B
Connectivity technology *	Wired & Wireless
Near Field Communication (NFC)	✔
Standard interfaces	Ethernet, NFC, USB, USB 1.1, USB 2.0

Network

Ethernet LAN *	✔

Features

Sound pressure level (printing)	55 dB
Cutter	✔
Autocutter durability	3 million cuts
Print head life	200 km
Country of origin	China

Design

Product colour *	Black

Power

Power source type *	AC
AC input voltage	24 V

Operational conditions

Operating temperature (T-T)	5 - 45 °C
Storage temperature (T-T)	-10 - 50 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	186 mm
Depth	278 mm
Height	181 mm
Weight	4.4 kg

Packaging data

Quantity per pack	1 pc(s)
Package width	294 mm
Package depth	385 mm
Package height	285 mm
Package weight	5.55 kg

Packaging content

Quick start guide	✔
AC adapter included	✔

Logistics data

Pallet weight (UK)	0 g
Harmonized System (HS) code	84433210
Products per pallet	56 pc(s)
Pallet gross weight	0 g
Products per pallet (UK)	70 pc(s)

Other features

Buffer size	4 KB
Electromagnetic compatibility	CE marking, EN55024, EN55032 Class A, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11, Directive 2014/30/EU
Print head life	200 million characters

8715946669977