

## Epson TM-M30II (121A0) 203 x 203 DPI Wired Direct thermal POS printer

**Brand :** Epson

**Product code:** C31CJ27121A0

**Product name :** TM-M30II (121A0)

Epson TM-M30II (121A0). Print technology: Direct thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 58 mm - 80 mm (Breite). Connectivity technology: Wired, USB connector: USB Type-A / USB Type-B. Ethernet LAN data rates: 10,100 Mbit/s. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Autocutter durability: 1.7 million cuts



<b>Printing</b>		<b>Operational conditions</b>	
Maximum resolution	203 x 203 DPI	Storage relative humidity (H-H)	10 - 90%
Print speed	250 mm/sec	<b>System requirements</b>	
Print speed (receipt)	250 mm/sec	Pre-installed software	TMNet WebConfig, ePOS-Device, ePOS-Display, ePOS-Print
Printing characters	Text, Graphic, Barcode	<b>Weight &amp; dimensions</b>	
Character sets	ANK	Width	127 mm
Print technology *	Direct thermal	Depth	127 mm
Type *	POS printer	Height	127 mm
<b>Paper handling</b>		Weight	1.3 kg
Maximum roll diameter	8.3 cm	<b>Packaging data</b>	
Supported paper width	58 mm - 80 mm (Breite)	Quantity per pack	1 pc(s)
<b>Ports &amp; interfaces</b>		Package width	195 mm
USB port *	✓	Package depth	235 mm
USB connector	USB Type-A / USB Type-B	Package height	235 mm
Connectivity technology *	Wired	Package weight	2.14 kg
Near Field Communication (NFC)	✓	<b>Packaging content</b>	
<b>Network</b>		AC adapter included	✓
Ethernet LAN *	✓	<b>Print technology</b>	
Ethernet LAN data rates	10,100 Mbit/s	Column capacity	48/57
<b>Features</b>		<b>Logistics data</b>	
Sound pressure level (printing)	55 dB	Pallet weight (UK)	0 g
Mean time between failures (MTBF)	360000 h	Harmonized System (HS) code	84433210
Half-cutter	✓	Products per master (outer) case	4 pc(s)
Autocutter durability	1.7 million cuts	Master (outer) case width	400 mm
Print head life	150 km	Master (outer) case length	490 mm
Country of origin	Philippines	Master (outer) case height	255 mm
Mounting position	Horizontal/Vertical		

Features		Logistics data	
Wall mountable	✓	Master (outer) case gross weight	0 g
Built-in sensors details	Paper End Sensor, Papier-Sensor	Products per pallet	128 pc(s)
Design		Pallet gross weight	0 g
Product colour *	White	Products per pallet (UK)	192 pc(s)
Power		Technical details	
Power plug type	Type G	Font styles	ANK
Operational conditions		Lifetime	15000000 lines
Operating temperature (T-T)	5 - 45 °C	Other features	
Storage temperature (T-T)	-20 - 60 °C	Buffer size	12 KB
Operating relative humidity (H-H)	10 - 90%	Mean cycles between failures (MCBF)	65000000
		Print head life	150.000.000 Impulse



8715946688541

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-FEB-2025. Prints or copies of Information are only valid on the printed Publication date