EPSON

Epson WorkForce DS-1660W Flatbed scanner 1200 x 1200 DPI A4 Black, White

Brand : Epson   **Product family:** WorkForce   **Product code:** B11B244401

Product name : DS-1660W

Epson WorkForce DS-1660W. Maximum scan size: 210 x 297 mm, Optical scanning resolution: 1200 x 1200 DPI, Enhanced scan resolution: 1200 x 1200 DPI. Scanner type: Flatbed scanner, Product colour: Black, White. Daily duty cycle (max): 1500 pages, Light source: ReadyScan LED, Scan file formats: JPG, PDF, TIFF. Auto document feeder (ADF) input capacity: 50 sheets. Maximum ISO A-series paper size: A4, ISO A-series sizes (A0...A9): A4, A5, A6, ISO B-series sizes (B0...B9): B5

Scanning

Maximum scan size *	210 x 297 mm
Optical scanning resolution *	1200 x 1200 DPI
Enhanced scan resolution	1200 x 1200 DPI
Colour scanning	✔
Duplex scanning *	✔
Input colour depth	30 bit
Output colour depth	24 bit
Input greyscale depth	10 bit
Output greyscale depth	8 bit
ADF scan speed (b/w, A4)	25 ppm
ADF scan speed (colour, A4)	25 ppm

Design

Scanner type *	Flatbed scanner
Product colour *	Black, White
Built-in display *	✘

Performance

Light source	ReadyScan LED
Scan file formats	JPG, PDF, TIFF
Daily duty cycle (max) *	1500 pages
Scan drivers	TWAIN
Password protection	✔
Scanning noise level	55 dB

Input capacity

Auto document feeder (ADF) input capacity	50 sheets

Paper handling

Maximum ISO A-series paper size *	A4
ISO A-series sizes (A0...A9)	A4, A5, A6
ISO B-series sizes (B0...B9)	B5
Letter	✔
Legal	✔
Auto Document Feeder (ADF) media weight	50 - 120 g/m²
Maximum scan area (ADF)	210 x 3048 mm
Minimum scan area (ADF)	89 x 127 mm

Packaging data

Quantity per pack	1 pc(s)
Package width	195 mm
Package depth	520 mm
Package height	405 mm
Package weight	4.84 kg

Packaging content

Software CD	✔
Warranty card	✔
Cables included	AC
Quick start guide	✔
Drivers included	✔
Bundled software	Epson Document Capture (Mac only), Epson Document Capture Pro (Windows only), Epson Document Capture Pro Server (on free download), Epson Scan 2

Sustainability

Sustainability certificates	ENERGY STAR

System requirements

Compatible operating systems	Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X, Mac OS X 10.6.8, Mac OS X 10.6.8 or later, Windows 10, Windows 7, Windows 7, 64-Bit-Version, Windows 8, Windows 8 (32/64 Bit), Windows 8.1, Windows 8.1 x64 Edition, Windows Vista, Windows Vista, 64-Bit-Version
Windows operating systems supported	Windows 10, Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64, Windows Vista, Windows Vista x64
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks

Operational conditions

Operating temperature (T-T)	10 - 35 °C

Ports & interfaces

USB port *	✔
USB version	3.2 Gen 1 (3.1 Gen 1)
Optional connectivity	Ethernet
Standard interfaces	USB 3.2 Gen 1 (3.1 Gen 1), Wireless LAN

Network

Wi-Fi	✔
Wi-Fi standards	802.11a, 802.11b, 802.11g
Ethernet LAN	✔
IPv6 support	✔
Supported network protocols	TCP/IP, DHCP, DNS, SNMP, SLP

Power

Power supply type *	AC

Weight & dimensions

Width	451 mm
Depth	318 mm
Height	121 mm
Weight	3.9 kg

Operational conditions

Storage temperature (T-T)	-20 - 80 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	20 - 80%

Other features

Control panel	5-line LCD with Push Scan features
Image formats supported	JPEG, TIFF
Cabling technology	10/100/1000Base-T(X)

Logistics data

Products per pallet	40 pc(s)
Country of origin	Indonesia
Pallet gross weight	0 g
Pallet gross length	120 cm
Pallet gross width	80 cm
Pallet gross height	15 cm
Products per pallet layer	8 pc(s)
Products per pallet layer (UK)	10 pc(s)
Products per pallet (UK)	50 pc(s)
Pallet weight (UK)	0 g
Pallet length (UK)	120 cm
Pallet width (UK)	100 cm
Pallet height (UK)	15 cm
Harmonized System (HS) code	84716070

8715946605661

4058154130742