iiyama

iiyama ProLite T2454MSC-B1AG tietokoneen litteä näyttö 60,5 cm (23.8") 1920 x 1080 pikseliä Full HD LED Kosketusnäyttö Monikäyttäjä musta

Tuotemerkki : iiyama   **Tuoteperhe:** ProLite   **Tuotekoodi:** T2454MSC-B1AG

Tuotteen nimi : T2454MSC-B1AG

iiyama ProLite T2454MSC-B1AG. Näytön halkaisija: 60,5 cm (23.8"), Näytön erottelutarkkuus: 1920 x 1080 pikseliä, HD-tyyppi: Full HD, Näytön teknologia: LED, Vasteaika (tyypillinen): 4 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäiset kaiuttimet. VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta

Display

Display diagonal *	60.5 cm (23.8")
Display resolution *	1920 x 1080 pixels
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	IPS
LED backlight	✔
Touchscreen *	✔
Touchscreen type	Multi-user
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness	250 cd/m²
Response time *	4 ms
Screen shape *	Flat
Supported graphics resolutions	640 x 480 (VGA), 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1440 x 900 (WXGA+), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080)
Aspect ratio	16:9
Contrast ratio (typical) *	1000:1
Contrast ratio (dynamic)	5000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.78 million colours
Pixel pitch	0.274 x 0.274 mm
Horizontal scan range	30 - 80 kHz
Vertical scan range	56 - 75 Hz
Display diagonal (metric)	60.5 cm

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘
Windows operating systems supported	✔

Ergonomics

Panel mounting interface	100 x 100 mm
Wall mountable	✔
Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✔
Height adjustment	7 cm
Tilt adjustment	✔
Tilt angle range	-5 - 90°
On Screen Display (OSD) languages	German, Dutch, English, Spanish, French, Italian, Japanese, Polish, Portuguese, Russian
Number of OSD languages	10
Plug and Play	✔

Power

Energy efficiency class (SDR) *	F
Energy consumption (SDR) per 1000 hours *	20 kWh
Power consumption (typical) *	24 W
Power consumption (standby) *	0.5 W
AC input voltage	100-240 V
AC input frequency	50 - 60 Hz
Power supply type	AC
Energy efficiency scale	A to G
European Product Registry for Energy Labelling (EPREL) code	366281

Operational conditions

Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Width (with stand)	540.5 mm
Depth (with stand)	128 mm
Height (with stand)	388 mm

Performance

Linux operating systems supported	✔
OmniTapps Multitouch compatibility	✘

Multimedia

RMS rated power	4 W
Built-in speaker(s) *	✔
Megapixel (approx.)	2.1 MP
Built-in microphone	✘
Built-in camera *	✘

Design

Product colour *	Black

Ports & interfaces

Number of upstream ports	1
USB Type-A downstream ports quantity	1
USB Touch port	✔
VGA (D-Sub) ports quantity	1
HDMI *	✔
HDMI ports quantity	1
Audio input	3.5mm
HDCP	✔

Ergonomics

VESA mounting *	✔

Weight & dimensions

Weight (with stand)	5.5 kg
Width (without stand)	540.5 mm
Depth (without stand)	46.5 mm
Height (without stand)	322.5 mm

Packaging content

Cables included	AC, HDMI, USB, VGA
Quick start guide	✔

Other features

International Protection (IP) code	IPX1
Dimensions (W x D x H) with stand	540.5 x 128 x 388 mm
Display viewable area (HxV)	527.04 x 296.46 mm
Placement supported	Horizontal/Vertical
Full HD	✔
Compliance certificates	RoHS
Mean time between failures (MTBF)	30000 h
Certification	CE, TÜV-Bauart, VCCI-B, EAC, ErP, WEEE, REACH, CB

Logistics data

Harmonized System (HS) code	85285210

4948570116416