Chieftec GPF-350P virtalähdeyksikkö 350 W 20+4 pin ATX TFX Hopea

Tuotemerkki : Chieftec

Tuotekoodi: GPF-350P

Tuotteen nimi : GPF-350P


Chieftec GPF-350P. Kokonaisteho: 350 W, AC-syöttöjännite: 115 - 230 V, AC-syöttötaajuus: 47 - 63 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Kaapelointityyppi: Ei-modulaarinen. Tarkoitus: PC, Virransyöttöyksikön mitat: TFX, Laakeritekniikka: Kaulus. Tuotteen väri: Hopea, Tuulettimen halkaisija: 8 cm, Tuulettimien määrä: 1 tuuletin(ta). Tuotteen leveys: 86 mm, Tuotteen syvyys: 175 mm, Tuotteen korkeus: 65 mm





Power		Ports & interfaces
Total power * AC input voltage * AC input frequency Input current Power factor	350 W 115 - 230 V 47 - 63 Hz 6.3 A 0.9	Peripheral (Molex) p connectors (4-pin) * CPU P4 connector (4 Floppy disk drive con Cabling type
Power Factor Correction (PFC) type	Active	Performance
Combined power (+3.3V) Combined power (+12V) Combined power (+5V) Combined power (-12V)	100 W 300 W 100 W 3.6 W	Purpose * Power supply unit (P * ATX version
Combined power (+5Vsb) Max output current (+3.3V) Max output current (+12V1)	10 W 16 A 15 A	Bearing technology Certification
Max output current (+12V1) Max output current (+12V2)	15 A	Design
Max output current (+5V) Max output current (-12V) Max output current (+5Vsb) Efficiency	16 A 0.3 A 2 A 85%	Product colour Fan diameter Number of fans On/off switch
Power protection features	Over voltage, Overload, Short	Weight & dimension
Ports & interfaces Motherboard power connector *	circuit 20+4 pin ATX	Width Depth Height
Number of SATA power connectors 2	2	Technical details

Ports & interfaces	
Peripheral (Molex) power connectors (4-pin) *	2
CPU P4 connector (4-pin)	1
Floppy disk drive connector	✓
Cabling type	Non-Modular
Performance	
Purpose *	PC
Power supply unit (PSU) form factor *	TFX
ATX version	2.3
Bearing technology	Sleeve
Certification	CE, CB, TUV
Design	
Product colour	Silver
Fan diameter	8 cm
Number of fans	1 fan(s)
On/off switch	×
Weight & dimensions	
Width	86 mm
Depth	175 mm
Height	65 mm
Technical details	
Compliance certificates	RoHS
Logistics data	
Harmonized System (HS) code	84733020



4710713234673

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.