

Verbatim 53652 ulkoinen kovalevy 1 TB 5400 RPM 2.5" USB Type-C 3.2 Gen 1 (3.1 Gen 1) Harmaa

Tuotemerkki : Verbatim

Tuotekoodi: 53652

Tuotteen nimi : 53652

Verbatim 53652. HDD-kapasiteetti: 1 TB, HDD-koko: 2.5". USB-versio: 3.2 Gen 1 (3.1 Gen 1). HDD-nopeus: 5400 RPM. Tuotteen väri: Harmaa



Hard drive		Weight & dimensions	
HDD capacity *	1 TB	Width	78 mm
HDD speed *	5400 RPM	Depth	132.2 mm
HDD size *	2.5"	Height	16 mm
Ports & interfaces		Weight *	173 g
USB data transfer rates	5000 Mbit/s	Packaging data	
Thunderbolt technology *	✗	Cables included	USB Type-A to USB Type-C
Wi-Fi *	✗	Interface adapters included	USB Type-A female - USB Type-C male
Ethernet LAN *	✗	User guide	✓
Maximum data transfer rate *	5000 Mbit/s	Bundled software	Nero Backup Software
USB connector *	USB Type-C	Package width	155 mm
USB version *	3.2 Gen 1 (3.1 Gen 1)	Package depth	34.5 mm
Features		Package height	155 mm
Product colour *	Grey	Package weight	254 g
Housing material	Aluminium, Plastic	Package type	Box
Plug and Play	✓	Logistics data	
LED indicators	Power	Harmonized System (HS) code	84717050
Windows operating systems supported	Windows 10, Windows 7, Windows 8	Pallet gross width	80 cm
		Pallet gross length	120 cm
		Pallet gross height	121 cm
		Pallet gross weight	322 kg
		Products per pallet	270 pc(s)
		Master (outer) case width	163 mm

Features		Logistics data	
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks	Master (outer) case length	200 mm
		Master (outer) case height	129 mm
		Master (outer) case net weight	1.15 kg
		Products per master (outer) case	4 pc(s)
Security		Other features	
Security algorithms	256-bit AES	Country of origin	China
Fingerprint reader	✓	Cable length	0.625 m
Hardware encryption	✓	Compliance certificates	CE, RoHS
Power			
Bus powered *	USB		
Bus power	5 V		
Operational conditions			
Operating temperature (T-T)	5 - 50 °C		
Storage temperature (T-T)	-40 - 70 °C		
Operating relative humidity (H-H)	5 - 90%		



0023942536529



023942536529

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.