

Delock WLAN Antenna 802.11 ac/a/b/g/n SMA 5 dBi omnidirectional joint black

Description

This WLAN antenna is designed to connect to devices with SMA interface, in order to send and receive WLAN dual band signals.



SMA

Specification

- Connector: SMA plug
- With flexible joint, rotatable
- Frequency range:
 - 2.4000 ~ 2.4835 GHz
 - 5.1500 ~ 5.7250 GHz
- Impedance: 50 Ohm
- Antenna gain: 5 dBi
- VSWR: 2.0 max.
- Operating temperature: -20 °C ~ 65 °C
- Length:
 - with flexible joint: ca.195 mm
 - without flexible joint: ca.165 mm
- Diameter:
 - peak: ca. 6.0 mm
 - SMA: ca. 12.5 mm

Item No. 89438

EAN: 4043619894383

Country of origin: Taiwan, Republic of China

Package: Poly bag





System requirements

- Device with SMA connector

Package content

- WLAN antenna SMA

Images



General	
Suitable for indoor:	yes
Operating temperature:	-20 °C ~ 65 °C
Interface	
Connection:	SMA plug
Technical characteristics	
Frequency range:	5.1500 GHz - 5.7250 GHz 2.4000 GHz - 2.4835 GHz
Gain:	5 dBi
Horizontal beam angle:	360°
Impedance:	50 Ohm
Polarisation:	linear vertical
VSWR:	2
Physical characteristics	
Diameter:	12.5 cm
Housing colour:	black
Housing:	TPEE
Length:	19.6 cm