

Epson EcoTank ET-16680 Mustesuihku A3 4800 x 1200 DPI Wi-Fi

Tuotemerkki : Epson

Tuotekoodi: C11CH71405

Tuotteen nimi : EcoTank ET-16680

EcoTank Pro ET-16680

Epson EcoTank ET-16680. Tulostustekniikka: Mustesuihku, Tulostus: Väritulostus, Suurin resoluutio: 4800 x 1200 DPI. Kopiointi: Värikopiointi, Kopiointin enimmäistarkkuus: 1200 x 1200 DPI. Skannaus: Väriskanuus, Optinen skannauserottelutarkkuus: 1200 x 1200 DPI. Faksaus: Värifaksaus. Kaksipuolinen toiminto: Tulosta, Skannaus. Suurin ISO A-luokan paperikoko: A3. Wi-Fi. Suoratulostus. Tuotteen väri: musta, Harmaa



Printing		Network	
Duplex printing mode	Auto	Mobile printing technologies	Epson Connect, Epson iPrint, Epson Email Print, Epson Remote Print, Apple AirPrint
Print technology *	Inkjet		
Printing *	Colour printing		
Duplex printing *	✓		
Maximum resolution *	4800 x 1200 DPI		
Print speed (ISO/IEC 24734) black	25 ppm		
Print speed (ISO/IEC 24734) colour	25 ppm		
Duplex print speed (black, normal quality, A4/US Letter)	21 ppm		
Duplex print speed (colour, normal quality, A4/US Letter)	21 ppm		
Duplex print speed (ISO/IEC 24734) mono	11.5 ipm		
Duplex print speed (ISO/IEC 24734) colour	6 ipm		
Duplex print speed (ISO/IEC 24734, A4) black	21 ppm		
Duplex print speed (ISO/IEC 24734, A4) colour	21 ppm		
Time to first page (black, normal)	5.5 s		
Time to first page (colour, normal)	5.5 s		
Copying		Performance	
Duplex copying *	✓	Sound pressure level (printing)	52 dB
Copying *	Colour copying	Sound power level (printing)	6.7 dB
Maximum copy resolution *	1200 x 1200 DPI		
Scanning		Design	
Duplex scanning *	✓	Product colour *	Black, Grey
Scanning *	Colour scanning	Market positioning *	Business
Optical scanning resolution *	1200 x 1200 DPI	Built-in display *	✓
Optical scanning resolution (ADF)	1200 x 1200 DPI	Display	LCD
Scanner type *	ADF scanner	Display diagonal	10.9 cm (4.3")
Scan to	Cloud	Touchscreen	✓
Scan speed (black)	26 inch/min	Control type	Buttons, Touch
Scan speed (colour)	9 inch/min	Colour display	✓
Image formats supported	BMP, JPEG, TIFF, PNG	Power	
Document formats supported	PDF	Power consumption (average operating)	19 W
		Power consumption (copying)	19 W
		Power consumption (ready)	9.7 W
		Power consumption (sleep)	0.7 W
		Power consumption (off)	0.15 W
		Energy Star Typical Electricity Consumption (TEC)	0.13 kWh/week
		AC input voltage	220 - 240 V
		AC input frequency	50 - 60 Hz
		System requirements	
		Windows operating systems supported	Windows 10, Windows 10 x64, Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64, Windows Vista, Windows Vista x64, Windows XP Professional x64, Windows XP
		Mac operating systems supported	✓

Fax		System requirements	
Duplex faxing	✓	Server operating systems supported	Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows Server 2016
Faxing *	Colour faxing	Mobile operating systems supported	Android, iOS 5.0, iOS 6.0, iOS 6.1, iOS 7.0, iOS 7.1, iOS 7.2, iOS 8.0, iOS 8.1, iOS 8.2, iOS 8.3, iOS 8.4, iOS 8.8, iOS 9.0, iOS 9.1, iOS 9.3
Fax transmission speed	3 sec/page		
Modem speed	33.6 Kbit/s		
Auto-redialing	✓		
Fax forwarding	✓		
Fax forwarding to	E-mail, PC		
Error Correction Mode (ECM)	✓		
Features		Weight & dimensions	
Maximum duty cycle *	66000 pages per month	Width	515 mm
Duplex functions *	Print, Scan	Depth	976 mm
Ink tank system	✓	Height	521 mm
Number of print cartridges *	4	Weight	21 kg
Printing colours *	Cyan, Magenta, Pigment black, Yellow	Packaging data	
Page description languages	PCL 5e, PCL 6	Package width	560 mm
Country of origin	Indonesia	Package depth	590 mm
Replacement cartridges	113 EcoTank Pigment	Package height	440 mm
		Package weight	24.6 kg
		Quantity per pack	1 pc(s)
Input & output capacity		Packaging content	
Total number of input trays *	3	Cartridge(s) included	✓
Total input capacity *	250 sheets	Included cartridge capacity (black)	7500 pages
Total output capacity *	125 sheets	Cables included	AC
Auto document feeder (ADF)	✓	Drivers included	✓
Auto document feeder (ADF) input capacity	50 sheets	Warranty card	✓
Maximum input capacity	550 sheets	Bundled software	Epson Device Admin (EDA), Epson Scan 2, Epson ScanSmart, Epson Status Monitor, EpsonNet Config
Paper handling		Logistics data	
Maximum ISO A-series paper size *	A3	Harmonized System (HS) code	84433100
Paper tray media types *	Envelopes, Letterhead, Thick paper, Thin paper	Pallet gross weight	0 g
ISO A-series sizes (A0...A9) *	A3, A3+, A4, A5, A6	Products per pallet	8 pc(s)
ISO B-series sizes (B0...B9)	B5, B6	Pallet weight (UK)	0 g
Non-ISO print media sizes	Legal, Letter	Products per pallet (UK)	8 pc(s)
Envelopes sizes	10, C4, C6, DL		
Paper tray media weight	64 - 255 g/m ²	Other features	
		Printing method	Epson PrecisionCore
Ports & interfaces			
Direct printing *	✓		
USB port	✓		
Optional connectivity	Ethernet, USB 2.0, Wireless LAN		
Network			
Wi-Fi *	✓		
Ethernet LAN *	✓		
Cabling technology	10/100Base-T(X)		
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)		
Security algorithms	64-bit WEP, 128-bit WEP, WPA-PSK, WPA-TKIP, WPA2-PSK, WPA2-AES		

Other features

Compatible operating systems	Android, Citrix XenApp 5.0, Citrix XenApp 6.0, Citrix XenApp 6.x, Citrix XenApp 7.6 und höher, Citrix XenApp 7.x, Citrix XenApp Version 6.5, Citrix XenApp Version 7.6, Citrix XenDesktop Version 7.6, Linux, MAC OS 10.15 + or later, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.2+, Mac OS 10.3+, Mac OS 10.4+, Mac OS ab Version 10.4.11 (nur Epson Scan), Mac OS 10.5+, Mac OS 10.5.8 oder höher, Mac OS 10.5.8 oder höher (Treiber muss von der Epson Website heruntergeladen werden), Mac OS 10.5.9, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X, Mac OS X 10.11.x, Mac OS X 10.11.x oder höher, Mac OS X 10.12, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Mac OS X 10.6.8 or later, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 Bit), Windows 8.1 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 Bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later, Windows XP Professional x64 Edition, iOS 5.0+, iOS 6.0+, iOS 7
Ink drop	3.8
Fax polling	✓
Print head nozzles	800 nozzles black, 800 nozzles per colour
Supported network protocols	HTTPS, IPv4, IPv6, SNMP
Noise level	52 dB



8715946690322

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-DEC-2024. Prints or copies of Information are only valid on the printed Publication date