Tuotemerkki: MSI

MSI MAG CORELIQUID 360R V2 Tietokoneen jäähdytysjärjestelmä Emolevy, Suoritin Nestejäähdytyspakkaus 12 cm musta

Tuotekoodi: MAG CORELIQUID 360R V2

Tuotteen nimi: MAG CORELIQUID 360R V2

MSI MAG CORELIQUID 360R V2. Malli: Nestejäähdytyspakkaus, Tuulettimen halkaisija: 12 cm, Pyörimisnopeus (min.): 500 RPM, Pyörimisnopeus (maks.): 2000 RPM, Pienin ilmanpaine: 0,23 mmH2O,

Suurin ilmanpaine: 2,39 mmH2O, Laakerityyppi: Kuulalaakeri. Tuotteen väri: musta





Performance		Design	
Suitable location * Type * Fan diameter	Liquid cooling kit 12 cm LGA 1150 (Socket H3), LGA 1151 (Socket H4), LGA 1155 (Socket H2), LGA 1156 (Socket H), LGA 1200 (Socket H5), LGA 1366 (Socket B), LGA 1700, LGA 2011 (Socket B), LGA 2011-v3 (Socket R), LGA 2066, Socket AM2, Socket AM2+, Socket AM3, Socket AM3+, Socket AM4, Socket FM1, Socket FM2, Socket FM2+, Socket FM2, Socket FM2+, Socket SP3, Socket TR4, Socket STRX4 AMD Ryzen 7 5th Gen, 3rd Generation AMD Ryzen™ 9, AMD Ryzen 9 5th Gen, 3rd Gen AMD Ryzen 9 5th Gen, 3rd Gen AMD Ryzen 9 5th Gen, 3rd Gen AMD Ryzen 1 Threadripper™, Intel® Core™ i7, Intel® Core™ i9 stational speed (max) 2000 RPM stational speed (max) 2000 RPM 21.63 cfm 78.73 cfm 0.23 mmH2O stimum air pressure stimum air pressure 2.39 mmH2O	Product colour * Radiator material Number of fans Illumination LED Fan connector	Black Aluminum 3 fan(s) 4-pin
Supported processor sockets		Power Fan power consumption Pump power consumption Pump voltage Pump current Fan voltage	1.8 W 4.08 W 12 V 340 mA 12 V
Compatible processor series		Fan current Weight & dimensions Radiator width	0.15 A 39.4 cm
Rotational speed (min) Rotational speed (max) Minimum airflow (imperial) Maximum airflow Minimum air pressure Maximum air pressure Fan diameter 2		Radiator depth Radiator height Tube length Waterblock width Waterblock depth Waterblock height Fan dimensions (W x D x H)	12 cm 2.7 cm 40 cm 8.06 cm 6.68 cm 4.86 cm 120 x 120 x 25 mm
Pulse-width modulation (PWM)	∠	Logistics data	
support Bearing type Fan noise level (min) Fan noise level (max) Pump noise level Fan bearing technology Pump bearing technology Pump connector Pump motor speed Fan speed (min) Fan speed (max)	Ball bearing 14.3 dB 34.3 dB 18 dB Ball bearing Ceramic bearing 3-pin 4200 RPM 500 RPM 2000 RPM	Harmonized System (HS) code	84733080





4526541039089

0824142262924



824142262924

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.