BenQ InstaShow WDC30 langaton esitysjärjestelmä HDMI Työpöytä

Tuotemerkki : BenQ   **Tuotekoodi:** 9H.JNY78.S1E

Tuotteen nimi : InstaShow WDC30

BenQ InstaShow WDC30. Kotelo: Työpöytä, Tuotteen väri: musta. Tuetut grafiikan erottelutarkkuudet: 800 x 600 (SVGA), 1280 x 1024 (SXGA), 1280 x 800 (WXGA), 1360 x 768 (WXGA), 1400 x 1050 (SXGA+),..., Tuetut videomoodit: 720p, 1080p, Suurin kuvataajuus: 60 fps. Antennityyppi: Ulkoinen, Antennin vahvistustaso (maks.): 5 dBi. Wi-Fi-standardit: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Langattoman LAN:in datansiirtonopeus (maksimi): 1750 Mbit/s, Wi-Fi-standardi: Wi-Fi 6 (802.11ax). Käyttöliittymä: HDMI

Design

Form factor *	Desktop
Product colour	Black
LED indicators	✔

Features

Supported graphics resolutions	800 x 600 (SVGA), 1280 x 1024 (SXGA), 1280 x 800 (WXGA), 1360 x 768 (WXGA), 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080)
Supported video modes	720p, 1080p
Maximum frame rate	60 fps
Number of simultaneously connected devices (max)	64
Security updates end date	31/12/2025

Antenna

Antenna type	External
Antenna gain level (max)	5 dBi
Antennas quantity	4

Network

Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)
Wi-Fi data rate (max)	1750 Mbit/s
Top Wi-Fi standard	Wi-Fi 6 (802.11ax)
Frequency band	2.4 / 5 GHz
Dual-band	✔
Ethernet LAN	✔
Ethernet LAN data rates	10,100 Mbit/s
Cabling technology	10/100Base-T(X)

Ports & interfaces

Audio (L/R) out	1
DC-in jack	✔

Power

Power source type *	DC
Output voltage	12 V
Output current	3.33 A
Power consumption (max)	12 W

System requirements

Windows operating systems supported	✔
Mac compatibility	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Storage temperature (T-T)	-10 - 60 °C
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Weight	1.73 kg
Package width	447 mm
Package depth	720 mm
Package height	177 mm
Package weight	11.9 kg

Packaging content

AC adapter included	✔
Cables included	HDMI
Quick start guide	✔

Network

Security algorithms	128-bit AES, WPA2, WPA2-PSK, WPA3
Maximum operating distance	30 m

Ports & interfaces

Interface *	HDMI
Number of HDMI outputs	2
HDMI version	2.0
Ethernet LAN (RJ-45) ports	1
USB 2.0 ports quantity	1

Logistics data

Country of origin	China
Products per pallet	144 pc(s)
Harmonized System (HS) code	8517620000

4718755085185

0840046044909

840046044909