

DELL P Series 24 Monitor - P2423D

Brand : DELL

Product family: P Series

Product code: DELL-P2423D

Product name : Dell 24 Monitor - P2423D

- 60.5cm (23.8") Quad HD 2560 x 1440 LED IPS - 5ms, 16:9, 300cd/m², 1000:1 - USB, HDMI, DisplayPort 60.5cm (23.8") Quad HD 2560 x 1440 LED IPS, 16:9, 300cd/m², 16.7M, 5ms, 178°/178°, 1000:1

DELL P Series 24 Monitor - P2423D:

Stay focused on a 23.8-inch QHD monitor optimized to deliver high performance details and clarity. DELL P Series 24 Monitor - P2423D. Display diagonal: 60.5 cm (23.8"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black






Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	Tilt adjustment	1
Display resolution *	2560 x 1440 pixels	Tilt angle range	-5 - 21°
HD type *	Quad HD	On Screen Display (OSD)	✓
Native aspect ratio *	16:9	Plug and Play	1
Display technology *	LCD	Power	
Panel type *	IPS		-
Backlight type	LED	Energy efficiency class (SDR) *	E
Touchscreen *	×	Energy efficiency class (HDR) *	Not available
Display brightness (typical)	300 cd/m ²	Energy consumption (SDR) per 1000 hours *	¹ 16 kWh
Response time *	5 ms	Power consumption (typical) *	16 W
Anti-glare screen	✓	Power consumption (standby) *	0.3 W
Screen shape *	Flat	Power consumption (max)	55 W
Supported video modes	480p, 576p, 720p, 1080i, 1080p, 1440p	Power consumption (off)	0.3 W
Contrast ratio (typical) *	1000:1	AC input voltage	100 - 240 V
Maximum refresh rate *	60 Hz	AC input frequency	50 - 60 Hz
Viewing angle, horizontal	178°	Input current	1.5 A
Viewing angle, vertical	178°	Power supply type	Internal
Display number of colours *	16.7 million colours	Energy efficiency scale	A to G
Response time (fast)	8 ms	European Product Registry for Energy Labelling (EPREL) code	1057427
Pixel pitch	0.2058 x 0.2058 mm		
Pixel density	123 ppi	Operational conditions	
Horizontal scan range	29 - 113 kHz	Operating temperature (T-T)	0 - 40 °C
Vertical scan range	49 - 75 Hz	Storage temperature (T-T)	-20 - 60 °C
Viewable size, horizontal	52.7 cm	Operating relative humidity (H-H)	10 - 80%
Viewable size, vertical	29.6 cm	Storage relative humidity (H-H)	5 - 90%
Viewable size diagonal	60.5 cm	Operating altitude	0 - 5000 m
High Dynamic Range (HDR) supported	×	Non-operating altitude	5000 - 12192 m

Display		Weight & dimensions	
Colour gamut standard	sRGB	Width (with stand)	537.8 mm
Colour gamut	99%	Depth (with stand)	179.6 mm
Performance		Height (with stand)	496.1 mm
NVIDIA G-SYNC *	×	Weight (with stand)	5.07 kg
AMD FreeSync *	×	Width (without stand)	537.8 mm
Low Blue Light technology	v	Depth (without stand) Height (without stand)	52.1 mm 318.5 mm
		Weight (without stand)	3.44 kg
Multimedia		Bezel width (side)	5.48 mm
Built-in speaker(s) *	×	Bezel width (top)	5.42 mm
Built-in camera *	×	Bezel width (bottom)	1.67 cm
Design		Packaging data	
Market positioning *	Business	Package weight	7.44 kg
Product colour *	Black	Packaging content	
Front bezel colour	Black	Stand included	1
Detachable stand	√	Cables included	AC, DisplayPort, USB
Feet colour	Silver	Sustainability	,,,
Ports & interfaces		Sustainability certificates	ENERGY STAR, TCO
Built-in USB hub *			
USB upstream port type	USB Type-B	Carbon footprint	
Number of USB Type-B upstream ports quantity	1	Total carbon footprint (kg of CO2e)	538
USB Type-A downstream ports quantity	4	Total carbon emissions, standard deviation (kg of CO2e)	128
HDMI *	1	Carbon emissions, manufacturing (kg of CO2e)	298
HDMI ports quantity	1	Carbon emissions, logistics (kg of	65
HDMI version	1.4	CO2e)	
DisplayPorts quantity	1	Carbon emissions, energy usage (kg of CO2e)	170
DisplayPort version	1.2	Carbon emissions, end-of-life (kg of	
Headphone out *	×	CO2e)	4
HDCP	✓	Total carbon emissions, w/o use phase (kg of CO2e)	368
AC (power) in	✓	PAIA version	1.3.0
Network		Other features	
Wi-Fi	×	Heavy metals free	Hg (mercury)
Ergonomics		Compliance certificates	RoHS
VESA mounting *	✓	Logistics data	
Panel mounting interface	100 x 100 mm	Harmonized System (HS) code	85285210
Cable lock slot *	 Image: A second s		00000200
Height adjustment *	1		
Adjustable height (max)	15 cm		
Pivot	1		
Pivot angle	90 - 90°		
Swivelling	1		
Swivel angle range	-45 - 45°		





5397184567968



5704174850250

5704174850243

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.