

## DELL P Series P2723D LED display 68,6 cm (27") 2560 x 1440 pikseliä Quad HD LCD musta, Hopea

Tuotemerkki : DELL Tuoteperhe: P Series Tuotekoodi: DELL-P2723D

Tuotteen nimi: P2723D

DELL P Series P2723D. Näytön halkaisija: 68,6 cm (27"), Näytön erottelutarkkuus: 2560 x 1440 pikseliä, HD-tyyppi: Quad HD, Näytön teknologia: LCD, Vasteaika (tyypillinen): 5 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta, Hopea





Display		Ergonomics	
Display diagonal * Display resolution * HD type * Native aspect ratio *	68.6 cm (27") 2560 x 1440 pixels Quad HD 16:9	On Screen Display (OSD) Plug and Play Power	1
Display technology * Panel type * Backlight type Touchscreen * Display brightness (typical) Response time * Anti-glare screen Screen shape * Supported video modes Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours *	LCD IPS LED  X 350 cd/m² 5 ms  Flat 480p, 576p, 720p, 1080i, 1080p, 1440p 1000:1 60 Hz 178° 178° 16.7 million colours 8 ms 0.2331 x 0.2331 mm 109 ppi 29 - 113 kHz 49 - 75 Hz 59.7 cm 33.6 cm 68.5 cm 68.5 cm	Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Input current Power supply type Energy efficiency scale European Product Registry for Energy Labelling (EPREL) code	E Not available 21 kWh 21 W 0.3 W 55 W 0.3 W 100 - 240 V 50 - 60 Hz 1.5 A Internal A to G 1057546
Response time (fast) Pixel pitch Pixel density Horizontal scan range Vertical scan range Viewable size, horizontal Viewable size, vertical Viewable size diagonal Display diagonal (metric)		Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions Width (with stand) Depth (with stand)	0 - 40 °C -20 - 60 °C 10 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m 611.6 mm 190.1 mm

Dienlay		Weight & dimensions	
Display High Dynamic Bango (HDB)		9	EDE 2 mm
High Dynamic Range (HDR) supported	×	Height (with stand) Weight (with stand)	535.2 mm 6.38 kg
sRGB coverage (typical)	100%	Width (without stand)	611.6 mm
Performance		Depth (without stand)	52.2 mm
		Height (without stand)	360.8 mm
NVIDIA G-SYNC *	X	Weight (without stand)	4.54 kg
AMD FreeSync *	×	Bezel width (side)	7.43 mm
Low Blue Light technology	<b>✓</b>	Bezel width (top)	7.37 mm
Multimedia		Bezel width (bottom)	1.78 cm
Built-in speaker(s) *	x	Packaging data	
Built-in camera *	X	Package weight	9.2 kg
Design		Packaging content	
Market positioning *	Home	Stand included	✓
Product colour *	Black, Silver	Cables included	AC, DisplayPort, USB Type-A to USB
Front bezel colour	Black	Quick start guide	Type-B  ✓
Detachable stand Feet colour	✓ Silver		•
	Silver	Sustainability	ENERGY STAR TOO
Ports & interfaces		Sustainability certificates  Doesn't contain	ENERGY STAR, TCO PVC/BFR
Built-in USB hub *	22 Car 1 (21 Car 1)		FVC/BIR
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Carbon footprint	
USB upstream port type Number of upstream ports	USB Type-B 1	Total carbon footprint (kg of CO2e)	586
USB Type-A downstream ports		Total carbon emissions, standard deviation (kg of CO2e)	137
quantity	4	Carbon emissions, manufacturing	200
HDMI *	✓	(kg of CO2e)	308
HDMI ports quantity	1	Carbon emissions, logistics (kg of	81
HDMI version	1.4	CO2e) Carbon emissions, energy usage (kg	
DisplayPorts quantity	1	of CO2e)	192
DisplayPort version	1.2	Carbon emissions, end-of-life (kg of	5
Headphone out *	×	CO2e)	3
HDCP	✓	Total carbon emissions, w/o use phase (kg of CO2e)	394
Network		PAIA version	1.3.0
Wi-Fi	x	Other features	
Ergonomics		Heavy metals free	Hg (mercury)
VESA mounting *	<b>✓</b>	Compliance certificates	RoHS
Panel mounting interface	100 x 100 mm	Logistics data	
Cable lock slot *	<b>✓</b>	Harmonized System (HS) code	85285210
Height adjustment *	<b>✓</b>		
Height adjustment	15 cm		
Pivot	<b>✓</b>		
Pivot angle	90 - 90°		
Swivelling	<b>✓</b>		
Swivel angle range	-45 - 45°		
Tilt adjustment	✓		
Tilt angle range	-5 - 21°		









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.