

DELL P Series P2423DE LED display 60,5 cm (23.8") 2560 x 1440 pikseliä Quad HD LCD musta

Tuotemerkki : DELL Tuoteperhe: P Series Tuotekoodi: DELL-P2423DE

Tuotteen nimi: P2423DE

DELL P Series P2423DE. Näytön halkaisija: 60,5 cm (23.8"), Näytön erottelutarkkuus: 2560 x 1440 pikseliä, HD-tyyppi: Quad HD, Näytön teknologia: LCD, Vasteaika (tyypillinen): 5 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäänrakennettu USB-keskus. VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta





Display		Ergonomics	
Display Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen *	60.5 cm (23.8") 2560 x 1440 pixels Quad HD 16:9 LCD IPS W-LED	Tilt adjustment Tilt angle range On Screen Display (OSD) Plug and Play LED indicators Power Energy efficiency class (SDR) *	✓ -5 - 21° ✓ ✓
Display brightness (typical) Response time *	300 cd/m² 5 ms	Energy efficiency class (BDR) * Energy consumption (SDR) per 1000 hours *	Not available
Anti-glare screen Screen shape * Supported video modes	✓ Flat 480p, 576p, 720p, 1080i, 1080p, 1440p	Power consumption (typical) * Power consumption (standby) * Power consumption (max)	20 W 0.3 W 170 W
Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch	1000:1 60 Hz 178° 178° 16.7 million colours 8 ms 0.2058 x 0.2058 mm	Power consumption (off) AC input voltage AC input frequency Input current Power supply type Energy efficiency scale European Product Registry for Energy Labelling (EPREL) code	0.3 W 100 - 240 V 50 - 60 Hz 2 A Internal A to G 1057583
Pixel density Horizontal scan range Vertical scan range Viewable size, horizontal Viewable size, vertical Viewable size diagonal Display diagonal (metric)	123 ppi 29 - 113 kHz 49 - 75 Hz 52.7 cm 29.6 cm 60.5 cm 60.45 cm	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	0 - 40 °C -20 - 60 °C 10 - 80% 5 - 90% 0 - 5000 m

Display		Weight & dimensions	
			527.0 mm
High Dynamic Range (HDR) supported	×	Width (with stand) Depth (with stand)	537.8 mm 179.6 mm
sRGB coverage (typical)	99%	Height (with stand)	496.1 mm
Performance		Weight (with stand)	5.55 kg
NVIDIA G-SYNC *	×	Width (without stand)	537.8 mm
		Depth (without stand)	52.1 mm
AMD FreeSync *	X	Height (without stand)	318.5 mm
Low Blue Light technology	✓	Weight (without stand)	3.92 kg
Multimedia		Bezel width (side)	5.48 mm
Built-in speaker(s) *	×	Bezel width (top)	5.42 mm
Built-in camera *	×	Bezel width (bottom)	1.67 cm
Design		Packaging data	
Market positioning *	Business	Package weight	7.97 kg
Product colour *	Black	Packaging content	
Front bezel colour	Black	Stand included	✓
Detachable stand	✓	Cables included	AC, DisplayPort, USB Type-A to USB
Feet colour	Silver		Type-C, USB Type-C to USB Type-C
Ports & interfaces		Quick start guide	✓
Built-in USB hub *	✓	Sustainability	
USB upstream port type	USB Type-C	Sustainability certificates	ENERGY STAR, TCO
Number of USB Type-C upstream	1	Doesn't contain	PVC/BFR
ports quantity	-	Carbon footprint	
USB Type-A downstream ports quantity	4	Total carbon footprint (kg of CO2e)	587
USB Type-C DisplayPort Alternate Mode	✓	Total carbon emissions, standard deviation (kg of CO2e)	140
USB Power Delivery up to	90 W	Carbon emissions, manufacturing	322
HDMI *	✓	(kg of CO2e)	
HDMI ports quantity	1	Carbon emissions, logistics (kg of CO2e)	70
HDMI version	1.4	Carbon emissions, energy usage (kg	191
DisplayPorts quantity	2	of CO2e)	131
DisplayPort version	1.4	Carbon emissions, end-of-life (kg of CO2e)	4
Headphone out *	×	Total carbon emissions, w/o use	206
HDCP	/	phase (kg of CO2e)	396
Charging port type	USB Type-C	PAIA version	1.3.0
AC (power) in	✓	Other features	
Network		Heavy metals free	Hg (mercury)
Wi-Fi	×	Compliance certificates	RoHS
Ergonomics		Ethernet LAN (RJ-45) ports	1
VESA mounting *	✓	Logistics data	
Panel mounting interface	100 x 100 mm	Harmonized System (HS) code	85285210
Cable lock slot *	✓		
Height adjustment *	✓		
Adjustable height (max)	15 cm		
Pivot	✓		
Pivot angle	90 - 90°		
Swivelling	✓		
Swivel angle range	-45 - 45°		









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.