## Allied Telesis 24 ports Managed Layer 3 Standalone Switch Hallittu L3



Tuotemerkki : Allied Telesis

Tuotekoodi: AT-9424T-50

Tuotteen nimi : 24 ports Managed Layer 3 Standalone Switch

Allied Telesis 24 ports Managed Layer 3 Standalone Switch. Kytkin tyyppi: Hallittu, Kytkinkerros: L3. Basic kytkentä RJ-45 Ethernet-porttien määrä: 20. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 96 Gbit/s. Verkkostandardit: IEEE 802.1d, IEEE 802.1D, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ac, IEEE 802.3ac, IEEE...

Management features		Protocols	
Switch type *	Managed	Management protocols	SNMP v1,v2,v3
Switch layer	L3	Performance	
Quality of Service (QoS) support	✓	Built-in processor	v
Web-based management	<ul> <li>Image: A start of the start of</li></ul>	Processor model	PowerPC
Ports & interfaces		Processor frequency	200 MHz
Basic switching RJ-45 Ethernet ports guantity *	<sup>5</sup> 20	Power	
Combo SFP ports quantity	4	Input current	2 - 4 A
SFP/SFP+ slots quantity	4	Input voltage	100 - 240 V
Network		Power consumption (typical)	54 W
Networking standards *	IEEE 802.1d, IEEE 802.1D, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	×
		Other features	
Port mirroring	✓	Dimensions (WxDxH)	438 x 304.8 x 44 mm
Full duplex	1	Connectivity technology	Wired
Link aggregation	1	Authentication method	RADIUS
Data transmission		Wi-Fi	X
Supported data transfer rates	10/100/1000 Mbps	Connectivity LEDs	
Switching capacity *	96 Gbit/s	Input frequency	50-60 Hz
Throughput	71.724 Mpps	Operational conditions	
MAC address table *	16000 entries	Operating temperature (T-T)	0 - 40 °C
Number of trunks	6	Storage temperature (T-T)	-25 - 70 °C
Maximum data transfer rate	1 Gbit/s	Operating relative humidity (H-H)	5 - 90%
Jumbo frames support	✓	Storage relative humidity (H-H) Operating altitude	5 - 90% 0 - 3048 m
Security			0 50-011
DHCP features	DHCP server, DHCP client	Weight & dimensions	4.21.1
MAC address filtering	✓	Weight	4.21 kg
Multicast features			
Multicast support	<ul> <li>Image: A set of the set of the</li></ul>		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.