

## Fujitsu Intel Xeon Gold 6136 suoritin 3 GHz 24,75 MB L3

Tuotemerkki : Fujitsu Tuotekoodi: S26361-F4051-E236

Tuotteen nimi: Intel Xeon Gold 6136

Fujitsu Intel Xeon Gold 6136. Suoritinperhe: Intel® Xeon® Gold, Prosessorin kanta: LGA 3647 (Socket P), Prosessorin litografia: 14 nm. Muistikanavat: Hexa-kanava, Prosessorin tukema suurin sisäinen muisti: 768 GB, Prosessorin tukemat muistityypit: DDR4-SDRAM. Markkinasegmentti: Palvelin, Tuetut ohjepaketit: AVX, AVX 2.0, AVX-512, SSE4.2, Skaalautuvuus: S4S. Prosessorin pakkauskoko: 76.0 x 56.5 mm



Processor		Features	
Processor generation  Processor model *  Processor base frequency *	1st Generation Intel® Xeon® Scalable 6136 3 GHz	PCI Express slots version Supported instruction sets Scalability Embedded options available	3.0 AVX, AVX 2.0, AVX-512, SSE4.2 S4S
Processor family *	Intel® Xeon® Gold	·	
Processor cores *	12	Processor special features	
Processor socket *	LGA 3647 (Socket P)	Intel® Hyper Threading Technology (Intel® HT Technology)	✓
Component for Processor lithography *	Server/workstation 14 nm	Intel® Turbo Boost Technology	2.0
Processor series	Intel Xeon Gold 6000 Series	Intel® AES New Instructions (Intel® AES-NI)	<b>✓</b>
Processor threads Processor operating modes *	24 64-bit	Enhanced Intel SpeedStep Technology	
Processor boost frequency	3.7 GHz	Intel Trusted Execution Technology	✓
Processor cache	24.75 MB	Intel® Speed Shift Technology	✓
Processor cache type Thermal Design Power (TDP)	L3 150 W	Intel VT-x with Extended Page Tables (EPT)	<b>/</b>
Stepping	H0	Intel TSX-NI	✓
Processor codename	Skylake	Intel 64	✓
Memory  Maximum internal memory		Intel Virtualization Technology (VT-x)	<b>✓</b>
supported by processor  Memory types supported by	768 GB	Intel Virtualization Technology for Directed I/O (VT-d)	
processor	DDR4-SDRAM	Conflict-Free processor	✓
Memory clock speeds supported by processor	2666 MHz	Intel Turbo Boost Max Technology 3.0	×
Memory channels *	Hexa-channel	Intel® Optane™ Memory Ready	×
ECC	✓	Intel® vPro™ Platform Eligibility	✓
Graphics		Operational conditions	
On-board graphics card *	×	Tcase	85 °C
Discrete graphics card *	×	Weight & dimensions	
On-board graphics card model *	Not available	Processor package size	76.0 x 56.5 mm
Features		110ccssor package size	70.0 7 50.5 111111
Execute Disable Bit	1		
Market segment	Server		
Maximum number of PCI Express lanes	48		

