

Lenovo ThinkSystem ST550 palvelin Torni (4U) Intel® Xeon Silver 4210R 2,4 GHz 16 GB DDR4-SDRAM 750 W

Tuotemerkki : Lenovo

Tuoteperhe: ThinkSystem

Tuotekoodi: 7X10A0E2EA



Tuotteen nimi : ST550

Lenovo ThinkSystem ST550. Suoritinperhe: Intel® Xeon Silver, Prosessorin taajuus: 2,4 GHz, Prosessorimalli: 4210R. Sisäinen muisti: 16 GB, Sisäisen muistin tyyppi: DDR4-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 16 GB. Ethernet LAN, Kaapelitekniikka: 10/100/1000Base-T(X). Virtalähde: 750 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Torni (4U)

Processor		Design	
Processor manufacturer *	Intel	Chassis type *	Tower (4U)
Processor family *	Intel Xeon Silver	Product colour	Black
Processor model *	4210R	Redundant fans support	1
Processor frequency *	2.4 GHz	Performance	
Processor boost frequency	3.2 GHz 13.75 MB	Performance management	XClarity Enterprise
Processor cache Motherboard chipset	Intel® C624	Trusted Platform Module (TPM)	 Image: A second s
Number of processors installed	1	Software	
Execute Disable Bit	-	Soltwale	Misrosoft Windows Conver, Ded Llat
Embedded options available	·	Compatible operating systems *	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi
Memory		Processor special features	
Internal memory *	16 GB	Enhanced Intel SpeedStep	
Internal memory type *	DDR4-SDRAM	Technology	1
Memory slots ECC	12x DIMM ✓	Intel Virtualization Technology for Directed I/O (VT-d)	 Image: A start of the start of
Memory clock speed	2933 MHz	Intel Trusted Execution Technology	1
Memory layout (slots x size)	1 x 16 GB	Intel VT-x with Extended Page	1
Storage		Tables (EPT)	
RAID support *	1	Intel 64	
RAID levels	0, 1, 5, 6, 10, 50, 60	Intel Virtualization Technology (VT- x)	1
Supported RAID controllers	9350-8i	Power	
Graphics			
•		Redundant power supply (RPS) support *	1
On-board graphics card	Matray C200	Power supply *	750 W
On-board graphics card model Maximum graphics card memory	Matrox G200 16 MB	Number of redundant power	1
	10 MB	supplies installed	1
Network		Logistics data	
Ethernet LAN	/	Harmonized System (HS) code	84714100
Cabling technology	10/100/1000Base-T(X)	Weight & dimensions	
Ports & interfaces		Width	176 mm
USB 2.0 ports quantity	5	Depth	660 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	3	Height	438 mm
ports quantity VGA (D-Sub) ports quantity	1	Weight	36 kg
VOA (D-Sub) poils qualities	Ţ		



5415247293811



8032976146675



5054444474113

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.