ASUS ROG-STRIX-750G power supply unit 750 W 20+4 pin ATX 1U

Brand: ASUS Product code: 90YE00A0-B0NA00

Product name: ROG-STRIX-750G

- ROG heatsinks cover critical components. Lower temps result in a longer lifespan and reduced noise
- Axial-tech fan design features a smaller fan hub that facilitates longer blades and a barrier ring that increases downward air pressure
- Dual ball fan bearings can last up to twice as long as sleeve bearing designs
- 0dB Technology lets you enjoy light gaming in relative silence
- An 80 Plus Gold Certification is the result of Japanese capacitors and other premium components
- Cosmetic customization is enabled by a magnetic logo and stickers that help you reskin the visible side to your liking
- Fully modular cables keep your rig neat and tidy

ATX12V, 80Plus Gold, 100-240Vac, 1.82Kg

ASUS ROG-STRIX-750G. Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX, Cabling type: Fully-Modular. Purpose: PC, Power supply unit (PSU) form factor: 1U, 80 PLUS certification: 80 PLUS Gold. Fan diameter: 13.5 cm. Cables included: AC, PCIe, SATA






Power		Performance	
Total power *	750 W	80 PLUS certification *	80 PLUS Gold
AC input voltage *	100 - 240 V	Purpose *	PC
AC input frequency	50 - 60 Hz	Power supply unit (PSU) form factor	10
Max output current (+3.3V)	20 A 62 A	*	
Max output current (+12V)		Design	
Max output current (+5V)	20 A	Fan diameter	13.5 cm
Max output current (-12V)	0.3 A	Packaging content	
Max output current (+5Vsb)	3 A		AC DCIa CATA
Power protection features	Over current, Over power, Over voltage, Overload	Cables included	AC, PCIe, SATA
		Weight & dimensions	
Ports & interfaces		Width	160 mm
Motherboard power connector *	20+4 pin ATX	Depth	150 mm
Number of SATA power connectors	8	Height	86 mm
Peripheral (Molex) power connectors (4-pin) *	3	Weight	1.82 kg
PCI Express power connectors (6+2 pin)	4	Packaging data	
		Package weight	3.14 kg
CPU power connector (4+4 pin)	√ Fully-Modular	Technical details	
Cabling type		Compliance certificates	RoHS
		Logistics data	
		Harmonized System (HS) code	84733020
		Other features	
		Cable ties included	✓









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.