ASUS ZenWiFi AX Mini (XD4) White 1PK Dual-band (2.4 GHz / 5 GHz) Wi-Fi 6 (802.11ax) 2 Internal

Brand : ASUS

Product code: 90IG05N0-MO3RM0

Product name : ZenWiFi AX Mini (XD4) White 1PK

AX1800 Whole-Home Mesh WiFi 6 System – Coverage up to 4,800 Sq. ft. / 5+ rooms, easy setup, life-time free network security & parental controls

ASUS ZenWiFi AX Mini (XD4) White 1PK. Product colour: White, Antenna type: Internal, Product type: Mesh router. Wi-Fi band: Dual-band (2.4 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 6 (802.11ax), WLAN data transfer rate (max): 1201 Mbit/s. Internal memory: 256 MB, Flash memory: 256 MB, Firewall security: Maximum Firewall keyword filter : 64 Maximum Firewall network service filter : 32 Maximum Firewall.... AC input voltage: 110 - 240 V, AC input frequency: 50 - 60 Hz, AC adapter output voltage: 12 V. Weight: 295 g





Design		Features	
Product type	Mesh router	Internal memory	256 MB
Product colour *	White	Flash memory	256 MB
LED indicators	Power	Quality of Service (QoS) support	1
Antenna type *	Internal	Port forwarding	1
Antennas quantity	2		Maximum Firewall keyword filter :
Reset button	v	Firewall security	64 Maximum Firewall network service filter : 32 Maximum Firewall URL filter : 64
Wireless LAN features			
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	DHCP server	1
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Parental control	1
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Works with Amazon Alexa	1
		Works with IFTTT	1
WLAN data transfer rate (max) *	1201 Mbit/s	МІМО	1
WLAN data transfer rate (first band)	574 Mbit/s	Protocols	
WLAN data transfer rate (second band)	1201 Mbit/s	Supported network protocols (IPv6)	yes
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Ports & interfaces	
		Ethernet LAN (RJ-45) ports *	2
Security algorithms	SSID, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3- PSK, WPS	Ethernet WAN	1
		Power	
Point-to-point protocol over	1	AC input voltage	110 - 240 V
Ethernet (PPPoE)	•	AC input frequency	50 - 60 Hz
IGMP snooping	1	AC adapter output voltage	12 V
Dynamic DNS (DDNS)	1	AC adapter output current	1.5 A
VPN support	VPN Client L2TP VPN Client OVPN VPN Client PPTP VPN Server IPSec VPN Server OVPN VPN Server PPTP	Weight & dimensions	
		Weight	295 g

Packaging content

Number of products included

1 pc(s)

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.