



## Canon i-SENSYS LBP233DW 1200 x 1200 DPI A4 Wi-Fi

**Tuotemerkki :** Canon

**Tuoteperhe:** i-SENSYS

**Tuotekoodi:** 5162C008

**Tuotteen nimi :** LBP233DW

Canon i-SENSYS LBP233DW. Tulostustekniikka: Laser. Värikasettien määrä: 1, Suurin toimintajakso: 80000 sivua kuukaudessa. Suurin resoluutio: 1200 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 33 ppm, Kaksipuolinen tulostus. Näyttö: LCD. Verkkovalmius, Wi-Fi. Tuotteen väri: musta, Valkoinen



| Printing  |   | Network   |  |
|---|---|---|--|
| Colour *  | ✗   | Ethernet LAN *                                    | ✓  |
| Print technology *                                  | Laser   | Cabling technology                                | 10/100/1000Base-T(X)   |
| Duplex printing *                                   | ✓   | Ethernet LAN data rates                           | 10,100,1000 Mbit/s   |
| Maximum resolution *                                | 1200 x 1200 DPI   | Wi-Fi standards                                   | 802.11b, 802.11g, Wi-Fi 4 (802.11n)  |
| Print speed (black, normal quality, A4/US Letter) * | 33 ppm  | Security algorithms                               | 64-bit WEP, 128-bit WEP, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPA2-TKIP |
| Warm-up time  | 14 s  | Mobile printing technologies                      | Apple AirPrint, Canon PRINT Business, Mopria Print Service                         |
| Time to first page (black, normal)                  | 5.5 s   |   |  |
| Features  |   | Performance                                       |  |
| Maximum duty cycle *                                | 80000 pages per month   | Internal memory *                                 | 1024 MB  |
| Recommended duty cycle                              | 750 - 4000 pages per month  | Sound pressure level (printing)                   | 54 dB  |
| Printing colours *                                  | Black   | Design  |  |
| Number of print cartridges *                        | 1   | Market positioning *                              | Business   |
| Page description languages *                        | PCL 5e, PCL 6, UFR II   | Product colour *                                  | Black, White   |
| Printer fonts                                       | PCL   | Built-in display *                                | ✓  |
| Input & output capacity                             |   | Display   | LCD  |
| Total number of input trays *                       | 1   | Control type                                      | Buttons  |
| Total input capacity *                              | 250 sheets  | Power   |  |
| Total output capacity *                             | 150 sheets  | Power consumption (max)                           | 1330 W   |
| Multi-Purpose tray                                  | ✓   | Power consumption (standby)                       | 9 W  |
| Multi-Purpose tray input capacity                   | 100 sheets  | Energy Star Typical Electricity Consumption (TEC) | 0.3 kWh/week   |
| Paper handling                                      |   | AC input voltage                                  | 220 - 240 V  |
| Maximum ISO A-series paper size *                   | A4  | AC input frequency                                | 50 - 60 Hz   |
| Maximum print size                                  | 216 x 356 mm  | System requirements                               |  |
| Paper tray media types *                            | Coated paper, Envelopes, Heavy paper, Labels, Plain paper, Postcard, Recycled paper, Thin paper | Windows operating systems supported               | Windows 10, Windows 11, Windows 8.1  |
| ISO A-series sizes (A0...A9) *                      | A4, A5  |   |  |
| ISO B-series sizes (B0...B9)                        | B5  |   |  |
| Non-ISO print media sizes                           | Index card, Legal, Letter, Oficio, Statement  |   |  |

| Paper handling                    |                           | System requirements               |  |
|-----------------------------------|---------------------------|-----------------------------------|--|
| Envelopes sizes                   | C5, Com-10, DL, Monarch   |                                   | Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 11.0 Big Sur |
| Paper tray media weight           | 60 - 120 g/m <sup>2</sup> |                                   |  |
| Ports & interfaces                |                           | Mac operating systems supported   |  |
| Direct printing *                 | ✓                         |                                   |  |
| USB port *                        | ✓                         |                                   |  |
| USB 2.0 ports quantity            | 1                         |                                   |  |
| Network                           |                           | Linux operating systems supported |  |
| Network ready                     | ✓                         |                                   | ✓  |
| Wi-Fi *                           | ✓                         |                                   |  |
| Operational conditions            |                           |                                   |  |
| Operating temperature (T-T)       |                           | 10 - 30 °C                        |  |
| Operating relative humidity (H-H) |                           | 20 - 80%                          |  |
| Weight & dimensions               |                           |                                   |  |
| Width                             |                           | 401 mm                            |  |
| Depth                             |                           | 373 mm                            |  |
| Height                            |                           | 250 mm                            |  |
| Weight                            |                           | 9.5 kg                            |  |
| Logistics data                    |                           |                                   |  |
| Harmonized System (HS) code       |                           | 84433210                          |  |



4549292186574

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-DEC-2024. Prints or copies of Information are only valid on the printed Publication date