

## ASUS P11C-M/4L Intel C242 LGA 1151 (Socket H4) micro ATX

**Brand :** ASUS

**Product code:** 90SB06R0-M0UAY0

**Product name :** P11C-M/4L

- Powered by the Intel Xeon E platform
  - 95W CPU and up to 64GB memory support (4 DIMMs)
  - Rack-optimized design maximizes cooling for excellent thermal efficiency
  - Flexible expandability with 6 native SATA HDDs and two PCIe Gen3 slots
  - Quad Intel I210AT Gigabit Ethernet with teaming support
  - Dual M.2 for up to 32Gbps performance and data redundancy
  - TPM-M 2.0 support for enhanced platform integrity
  - Complete server management with ASUS Control Center
  - Optional ASMB9-iKVM module available for 24/7 remote monitoring and diagnostics
- Micro-ATX, LGA1151, Intel C242, 4x DDR4 2400/2666, PCI-E x8/x16, 6x SATA3, 4x Intel I210AT, Aspeed AST2500 32MB, USB 3.1, VGA



<b>Processor</b>		<b>Rear panel I/O ports</b>	
Processor manufacturer *	Intel	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2
Processor socket *	LGA 1151 (Socket H4)	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	2
Compatible processor series *	Intel® Celeron®, Intel® Core™ i3, Intel® Pentium®, Intel® Xeon®	Ethernet LAN (RJ-45) ports *	4
<b>Memory</b>		VGA (D-Sub) ports quantity *	1
Supported memory types *	DDR4-SDRAM	<b>Network</b>	
Number of memory slots *	4	Ethernet LAN	✓
Memory slots type	DIMM	LAN controller	Intel® I210-AT
Memory channels	Dual-channel	<b>Features</b>	
ECC compatibility	ECC & Non-ECC	Motherboard chipset *	Intel C242
Supported memory clock speeds	2400,2666 MHz	Component for *	PC
Maximum internal memory *	64 GB	Motherboard form factor *	micro ATX
<b>Graphics</b>		Motherboard chipset family *	Intel
Graphics card	AST2500	<b>Expansion slots</b>	
<b>Internal I/O</b>		PCI Express x8 slots	1
USB 2.0 connectors *	1	PCI Express x16 slots	1
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	Number of M.2 (M) slots	2
Number of SATA III connectors *	6	<b>Operational conditions</b>	
ATX Power connector (24-pin)	✓	Storage temperature (T-T)	10 - 35 °C
Number of chassis fan connectors	5	Operating temperature (T-T)	-40 - 70 °C
EPS power connector (8-pin)	✓	Operating relative humidity (H-H)	20 - 90%
<b>Logistics data</b>		<b>Weight &amp; dimensions</b>	
Harmonized System (HS) code		84733020	
Width		244 mm	

## Weight & dimensions

Depth 244 mm



4718017055451



0192876055458



192876055458

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.