

AXIS Q1715 Block Camera

High performance with endless options

AXIS Q1715 delivers HDTV 1080p at 60 fps and 21x optical zoom for all the details. With a deep learning processing unit, it's possible to take advantage of intelligent tailor-made applications based on deep learning on the edge. It comes with AXIS Object Analytics for highly nuanced object classification and reliable detection with fewer false positives. And, it provides analytics metadata based on deep learning on the edge. Lightweight in design, it's easy to install in accessory housings and casings. It offers support for 2-way audio and supervised I/O. Furthermore, it features built-in cybersecurity features to prevent unauthorized access and safeguard your system.

- > **1080p at 60 fps with 21x zoom**
- > **Support for analytics with deep learning**
- > **Granular object classification**
- > **Ideal for accessory housings and casings**
- > **HDMI and HD-SDI output**



AXIS Q1715 Block Camera

Camera	
Image sensor	1/2.8" progressive scan RGB CMOS
Lens	Varifocal, 4–84.6 mm, F1.6–F4.5 Horizontal field of view: 76°–3.6° Vertical field of view: 42°–2.2° Autofocus, P-Iris control
Day and night	Automatically removable infrared-cut filter
Minimum illumination	1080p 25/30 fps with Forensic WDR and Lightfinder 2.0: Color: 0.1 lux at 50 IRE F1.5 B/W: 0.02 lux at 50 IRE F1.5 1080p 50/60 fps with Forensic WDR and Lightfinder 2.0: Color: 0.2 lux at 50 IRE F1.5 B/W: 0.04 lux at 50 IRE F1.5
Shutter speed	1/66500 s to 2 s
Pan/Tilt/Zoom	Zoom: 21x optical 100 preset positions, control queue, adjustable zoom speed Uploadable PTZ driver
System on chip (SoC)	
Model	ARTPEC-7
Memory	2048 MB RAM, 1024 MB Flash
Compute capabilities	Deep learning processing unit (DLPU)
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG
Resolution	1920x1080 HDTV 1080p to 160x90
Frame rate	Up to 60/50 fps (60/50 Hz) in all resolutions HDMI and HD-SDI are limited to 30 fps in 1080p
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Video streaming indicator
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: up to 120 dB depending on scene, white balance, day/night threshold, tone mapping, local contrast, EIS, exposure mode, exposure zones, defogging, compression, rotation: auto, 0°, 90°, 180°, 270° including Corridor Format, dynamic text and image overlays, polygon privacy mask, mirroring of images Scene profiles: forensic, vivid, traffic overview
Audio	
Audio encoding	SDI: AES3 24 bit, 48 kHz HDMI: LPCM 24 bit, 48 kHz Network: AAC-LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 48 kHz
Audio input/output	External microphone input or line input, ring power, network speaker pairing
Network	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, signed video, Axis Edge Vault, Axis device ID, secure keystore (CC EAL4 certified), TPM (FIPS 140-2 certified)
Supported protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^a , HTTP/2, TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, DHCPv4/v6, SOCKS, SSH, SIP, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)
System integration	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org

	Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.
Event conditions	Audio: audio clip playing, audio detection Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address removed, network lost, new IP address, ring power overcurrent protection, storage failure, system ready, within operating temperature, shock detection Digital audio: digital signal contains Axis metadata, digital signal has invalid sample rate, digital signal missing, digital signal OK Edge storage: recording ongoing, storage disruption I/O: digital input, manual trigger, virtual input MQTT subscribe PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: average bitrate degradation, day-night mode, live stream open, tampering
Event actions	Record video: SD card and network share MQTT publish Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation, play audio clip, zoom preset, day/night mode, make call
Data streaming	Event data
Built-in installation aids	Leveling guide, pixel counter, license plate capture assistant
Analytics	
AXIS Object Analytics	Object classes: humans, vehicles (types: cars, buses, trucks, bikes) Trigger conditions: line crossing, object in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
Applications	Included AXIS Object Analytics AXIS Video Motion Detection Supported AXIS Audio Spectrum Visualizer Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
General	
Casing	Aluminum and plastic casing Color: NCS S 9000-N
Sustainability	PVC free, BFR/CFR free
Power	Power over Ethernet (PoE) IEEE 802.3at Type 2 Class 4 10–28 V DC, typical 12 W, max 13.5 W
Connectors	Shielded RJ45 10BASE-T/100BASE-TX/1000BASE-T PoE I/O: 6-pin 2.5 mm terminal block for four configurable inputs RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block 3.5 mm mic/line in, 3.5 mm line out DC input HDMI Type A, BNC for SDI I2C for AXIS TQ1809-LE Housing
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–85% RH (non-condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)

Approvals	<p>EMC EN 55035, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KS C 9832 Class A, KS C 9835, RCM AS/NZS CISPR 32 Class A, VCCI Class A</p> <p>Safety CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 62368-1, IS 13252</p> <p>Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78</p> <p>Network NIST SP500-267</p>
Dimensions	Height: 66 x 80 x 195 mm (2.6 x 3.1 x 7.7 in)
Weight	650 g (1.4 lb)
Included accessories	Installation guide, Windows® decoder 1-user license, stand, connector kit, TORX® T20 screw driver, RESISTORX® L-key, terminal block connector

Optional accessories	<p>AXIS TQ1809-LE Housing T92G^b AXIS T8415 Wireless Installation Tool AXIS Surveillance Cards For more accessories, see axis.com</p>
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese
Warranty	5-year warranty, see axis.com/warranty

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*
- b. *The HDMI and SDI outputs are not available when the camera is mounted in the TQ1809-LE Housing.*

Environmental responsibility:

axis.com/environmental-responsibility