



## Jabra Engage 55 - USB-C MS Stereo, EMEA/APAC

**Brand :** Jabra

**Product code:** 9559-470-111

**Product name :** Jabra Engage 55 - USB-C MS Stereo, EMEA/APAC

- Up to 13 hours battery life
- Great for long wireless calls
- Incredible wireless range
- USB adapter (no base)
- Durable, portable
- 1 year limited warranty
- Passive Noise-Cancellation
- Goes beyond the highest DECT Security Level C
- 3 wearing styles
- 52 Hours standby
- Up to 150m DECT wireless range
- Stereo sound & wideband audio, optimised for speech clarity
- Durable USB DECT adapter is designed for portability
- SafeTone™ 2.0 for outstanding hearing protection
- Works with all leading UC and contact centre platforms

Jabra Engage 55 - USB-C MS Stereo, EMEA/APAC

[Jabra Engage 55 - USB-C MS Stereo, EMEA/APAC:](#)

Jabra Engage 55 is ideal for hybrid workers who spend most of their day on calls or virtual meetings. With a lightweight, comfortable design for all-day wear, outstanding wireless range and robust DECT Level C security, it's the perfect headset for hybrid working.



Performance		Microphone	
Product type *	Headset	Microphone type *	Boom
Wearing style *	Head-band	Microphone frequency	100 - 7300 Hz
Recommended usage *	Office/Call center	Microphone direction type	Unidirectional
Headset type	Binaural	Number of microphones	2
Product colour *	Black, Titanium	MEMS (Micro-Electro-Mechanical System) microphone	✓
Operating keys	Answer/end call, Mute, Volume +, Volume -	Microphone mute	✓
Volume control	Button	<b>Battery</b>	
Control unit type	On-ear control unit	Battery operated	✓
Control type	Buttons	Battery type	Built-in battery
DECT connectable	✓	Battery technology	Lithium-Ion (Li-Ion)
Hearing protection technologies	Jabra PeakStop, Jabra SafeTone, Jabra Safetone G616	Continuous audio playback time	13 h
HD voice	✓	<b>Operational conditions</b>	
<b>Ports &amp; interfaces</b>		Operating temperature (T-T)	-5 - 45 °C
Connectivity technology *	Wireless	Storage temperature (T-T)	-10 - 55 °C
USB connectivity	✓	<b>Weight &amp; dimensions</b>	
Frequency response (music mode)	40 - 16000 Hz	Weight	83 g
Frequency response (talk mode)	150 - 6800 Hz	<b>Packaging content</b>	
Wireless range	150 m	Receiver included	✓
<b>Headphones</b>		Wireless receiver interface	USB Type-C
Ear coupling *	Supraaural	Pouch	✓
		Quantity	1
		<b>Logistics data</b>	
		Harmonized System (HS) code	85183000



5706991025675

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-FEB-2025. Prints or copies of Information are only valid on the printed Publication date