



APC SRTG8KXLI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 8 kVA 8000 W 3 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRTG8KXLI

Tuotteen nimi : SRTG8KXLI

APC SRTG8KXLI. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 8 kVA, Lähtöteho: 8000 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Hardwire, Ulostulojen määrä: 3 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun jännite: 96 V, Akun kestoikä (maks.): 5 vuosi/vuosia. Kotelo: Telineasennettava/Torni, Näytön tyyppi: LCD, International Protection (IP)-koodi: IP20. Sertifiointi: CE, EN/IEC 62040-1




Features		Battery	
UPS topology *	Double-conversion (Online)	Number of batteries supported	2
Output power capacity *	8 kVA	Battery life (max)	5 year(s)
Output power *	8000 W	Battery recharge time	4 h
Waveform *	Sine	Hot-swap battery	✓
Input operation voltage (min) *	100 V	Automatic battery test	✓
Input operation voltage (max) *	285 V	Cold start	✓
Input frequency *	40/70 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
ECO mode	✓		
Output voltage Total Harmonic Distortion (THD)	2%		
Noise level	55 dB		
Audible alarm(s)	✓		
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm		
Auto-restart	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler, C19 coupler	Form factor *	Rackmount/Tower
Power plug	Hardwire	Display type	LCD
AC outlets quantity	3 AC outlet(s)	LED indicators	✓
USB port	✓	International Protection (IP) code	IP20
Serial interface	✓		
Ethernet LAN (RJ-45) ports	1		
Emergency Power Off (EPO) connector	✓		
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 2011.68 m
		Non-operating altitude	0 - 15240 m
		Certificates	
		Certification	CE, EN/IEC 62040-1
		Weight & dimensions	
		Width	440 mm
		Depth	620 mm
		Height	217 mm
		Weight	81.1 kg

Battery

Battery technology Sealed Lead Acid (VRLA)
Battery voltage 96 V

Packaging data

Package width 590 mm
Package depth 790 mm
Package height 414 mm
Package weight 83.1 kg



0731304411840



731304411840

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.