

## EZVIZ HB8 Pallomainen IP-turvakamera Sisätila ja ulkotila 2560 x 1440 pikseliä Katto

Tuotemerkki: EZVIZ Tuotekoodi: CS-HB8-R100-2C4WDL

Tuotteen nimi: HB8

EZVIZ HB8. Malli: IP-turvakamera, Tuettu sijoitus: Sisätila ja ulkotila, Yhteysteknologia: Langaton. Kiinnitystyyppi: Katto, Tuotteen väri: Valkoinen, Kotelo: Pallomainen. Objektiivin kuvakulma, vaakasuora: 83°, Objektiivin kuvakulma, pystysuora: 44°, Objektiivin kuvakulma, kulmittain: 100°. Anturin tyyppi: CMOS, Optisen sensorin koko: 25,4 / 3 mm (1 / 3"). Linssin halkaisija: 4 mm





Performance		Network	
Type * Placement supported * Connectivity technology * Auto-tracking Day/night mode Infrared (IR) cut-off filter	IP security camera Indoor & outdoor Wireless	Wi-Fi standards Wi-Fi data rate (max) Bluetooth * Channel bandwidth Works with the Google Assistant Works with Amazon Alexa	802.11b, 802.11g, Wi-Fi 4 (802.11n) 150 Mbit/s  X 20 MHz  ✓
Built-in light Operating frequency Design	✓ 2400 - 2483.5 MHz	Storage Built-in HDD *	×
Form factor *  Mounting type *  Product colour *  Weatherproof	Spherical Ceiling White	Card reader integrated Flash memory  Ports & interfaces  USB port	X 32000 MB
Camera		Security	
Camera pan control Camera tilt control Minimum illumination Lens viewing angle, horizontal Lens viewing angle, vertical Lens viewing angle, diagonal Tilt angle range Pan range Adjustment shutter speed	0 lx 83° 44° 100° -65 - 65° 0 - 340°	Built-in siren Password protection Video motion detection Security algorithms Anti-flicker Heartbeat Digital watermark	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
Adjustifient shatter speed	Auto	Management features  Reset button	<b>✓</b>

Image sensor		Power	
Number of sensors Optical sensor size Progressive scan Sensor type *	1 25.4 / 3 mm (1 / 3") CMOS	Power source type * Power consumption (max) Battery technology Battery capacity Rechargeable battery	Battery 10 W Lithium-lon (Li-lon) 10400 mAh
Lens system	1	Operational conditions	
Number of lenses * Lens diameter Focus adjustment	1 4 mm 1.6	Operating temperature (T-T) Operating relative humidity (H-H)	-20 - 50 °C 0 - 95%
Night vision		Weight & dimensions	
Night vision * Night vision distance	<b>√</b> 15 m	Width Depth Height	116 mm 183 mm 166 mm
Video		Weight	803 g
Maximum resolution * Total megapixels *	2560 x 1440 pixels 4 MP	Packaging data	
Video compression formats Frame rate Noise reduction Noise reduction technology	H.264, H.265 15 fps ✓ 3D noise reduction	Package width Package depth Package height Package weight	216 mm 145 mm 203 mm 1.06 kg
Bit rate	2 Mbps	Sustainability	
Audio		Sustainability compliance Compliance certificates	✓ CE, REACH, RoHS, WEEE
Built-in speaker(s) Audio system	✓ 2-way	Packaging content	CE, REACH, ROHS, WEEE
Built-in microphone	<b>√</b>	Number of cameras *	1
Network		Cables included	USB
Ethernet LAN * Wi-Fi *	×	Screws included Drilling template included Manual	<i>* *</i>

