Samsung OM55N-DS Digital signage flat panel 139.7 cm (55") LCD Wi-Fi 3000 cd/m² Full HD Black Built-in processor Tizen 5.0

Brand : Samsung **Product family:** OMN-DS **Product code:** LH55OMNDSGBXEN

Product name: OM55N-DS

55", VA, FHD (1920 x 1080), 3000 nit, 6000:1, 178/178, 6 ms, WiFi, RJ-45, HDCP, HDMI, RS232, AC 100-240V, 50/60Hz, 726.8 x 1299 x 69.5 mm, 42 kg

Samsung OM55N-DS. Product design: Digital signage flat panel. Display diagonal: 139.7 cm (55"), Display technology: LCD, Display resolution: 1920 x 1080 pixels, Display brightness: 3000 cd/m², HD type: Full HD. Wi-Fi. Operating system installed: Tizen 5.0. Product colour: Black





Display		Design	
VA Display diagonal * 139.7 cm (55") Display technology * LCD Display resolution * 1920 x 1080 pixels	139.7 cm (55") LCD	Screen shape Bezel width (bottom) Bezel width (side) Bezel width (top)	Flat 2.28 cm 2.28 cm 2.28 cm
Display brightness *	3000 cd/m ²	Performance	
HD type * Touchscreen * Response time Contrast ratio (typical)	Full HD X 6 ms 6000:1 Mega Contrast	Purpose * HDCP HDCP version	Universal ✓ 2.2
Dynamic contrast ratio marketing		Power	
name Viewing angle, horizontal Viewing angle, vertical 178° 178°	178° 178° 0.63 x 0.63 mm	Power consumption (typical) * Power consumption (sleep) AC input voltage AC input frequency	500 W 0.5 W 100 - 240 V 50 - 60 Hz
Horizontal scan range	15 - 135 kHz	Computer system	
Vertical scan range 24 - 75 Hz Pixel frequency (max) 594 MHz RGB colour space NTSC Colour gamut 72%	594 MHz NTSC	Computer system * Computer system type Built-in processor *	System on Chip (SoC)
Ports & interfaces		Operating system installed	Tizen 5.0
HDMI ports quantity * HDMI version DVI port * USB port * USB ports quantity	MI version 2.0 port * B port *	Weight & dimensions Display width Display depth Display height Display weight	726.8 mm 69.5 mm 1299 mm 42 kg
Ethernet LAN *	<u>-</u> ✓	Packaging data	
Ethernet LAN (RJ-45) ports Wi-Fi * RS-232 interface Infrared data port	1 ✓	Package width Package depth Package height Package volume	940 mm 367 mm 1466 mm 52000 cm ³
Remote (IR) input	1	Operational conditions	
Product design * Placement supported *	Digital signage flat panel	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 10 - 80%

Design		Certificates	
Orientation	Vertical	Certification	Class A 60950-1
Product colour *	Black	Other features	
		Flash memory	8000 MB
		RS-232 input ports	1



8806094036091

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.