

QNAP QHora-322 langallinen reititin 2.5 Gigabit Ethernet, 10 Gigabit Ethernet Valkoinen

Tuotemerkki : QNAP

Tuotekoodi: QHORA-322

Tuotteen nimi : QHora-322



QNAP QHora-322. Verkkostandardit: IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, Ethernet-liitännän tyyppi: 2.5 Gigabit Ethernet, 10 Gigabit Ethernet, Ethernet LAN - datanopeudet: 100,1000,2500,5000,10000 Mbit/s. USB-versio: 3.2 Gen 1 (3.1 Gen 1). Palomuurisuojaus: TCP, UDP, ICMP, TCP+UDP, VPN-tuki: L2TP, WireGuard, OpenVPN, QBelt. Sisältää johdot: AC, LAN (RJ-45). Suoritinvalmistaja: Marvell, Prosessorimalli: CN9130, Prosessorin taajuus: 2,2 MHz

WAN connection		Security	
Ethernet WAN *	✓	VPN support	L2TP, WireGuard, OpenVPN, QBelt
DSL WAN *	✗	Packaging content	
SIM card slot *	✗	AC adapter included	✓
3G/4G USB modem compatibility *	✗	Cables included	AC, LAN (RJ-45)
SFP WAN *	✗	Quick installation guide	✓
Network		Features	
Networking standards *	IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x	Built-in processor	✓
Ethernet interface type *	2.5 Gigabit Ethernet, 10 Gigabit Ethernet	Processor manufacturer	Marvell
Ethernet LAN data rates	100,1000,2500,5000,10000 Mbit/s	Processor model	CN9130
Full duplex	✓	Processor frequency	2.2 MHz
VLAN support	✓	Storage media	Flash
Flow control support	✓	Internal storage capacity	4 GB
Traffic control	✓	Flash memory	4 MB
Port forwarding	✓	Internal memory	4096 MB
Concurrent connections	50000	Internal memory type	DDR4
Management features		Certification	CE / FCC / VCCI / BSMI / RCM / CCC / UKCA
Quality of Service (QoS) support	✓	Design	
Reset button	✓	Product colour *	White
Ports & interfaces		LED indicators	✓
Ethernet LAN (RJ-45) ports *	9	Power	
USB ports quantity	1	Power consumption (typical) *	36 W
USB version	3.2 Gen 1 (3.1 Gen 1)	Power source type	DC
DC-in jack	✓	Output voltage	12 V
Protocols		Operational conditions	
DMZ support	✓	Operating temperature (T-T)	0 - 40 °C
Security		Operating relative humidity (H-H)	5 - 95%
Firewall	✓	Weight & dimensions	
Firewall security	TCP, UDP, ICMP, TCP+UDP	Width	226 mm
Network address translation (NAT)	✓	Depth	140 mm
		Height	44.4 mm
		Weight	1.08 kg

Security

System event log

**Packaging data**

Package weight

1.61 kg



4713213519950

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date