



Lenovo ThinkSystem ST650 V2 server Tower (4U) Intel Xeon Silver 4310 2.1 GHz 32 GB DDR4-SDRAM 750 W



Brand : Lenovo

Product family: ThinkSystem

Product code: 7Z74A02SEA

Product name : ST650 V2

- No OS
 - Intel Xeon Silver 4310 (18MB Cache, 2.1GHz)
 - 32GB (3200MHz) DDR4-SDRAM (1 x 32)
- ThinkSystem ST650 V2 Tower Server

Lenovo ThinkSystem ST650 V2 server Tower (4U) Intel Xeon Silver 4310 2.1 GHz 32 GB DDR4-SDRAM 750 W:

Enterprise performance and flexibility. Compact footprint.

ThinkSystem ST650 V2 is a highly capable 4U tower server that provides the performance and reliability you expect from the data center, optimized for office environments. Named CRN's Product of the Year for 2022.

Lenovo ThinkSystem ST650 V2. Processor family: Intel Xeon Silver, Processor frequency: 2.1 GHz, Processor model: 4310. Internal memory: 32 GB, Internal memory type: DDR4-SDRAM, Memory layout (slots x size): 1 x 32 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 750 W, Redundant power supply (RPS) support. Chassis type: Tower (4U)

Processor		Design	
Processor manufacturer *	Intel	Product colour	Black
Processor family *	Intel Xeon Silver	Rack mounting	✓
Processor model *	4310	Performance	
Processor frequency *	2.1 GHz	Performance management	XClarity Enterprise
Processor boost frequency	3.3 GHz	Trusted Platform Module (TPM)	✓
Processor cache	18 MB	Trusted Platform Module (TPM) version	2.0
Number of processors installed	1	Software	
Memory		Operating system installed *	✗
Internal memory *	32 GB	Compatible operating systems *	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi
Internal memory type *	DDR4-SDRAM	Power	
Memory clock speed	3200 MHz	Redundant power supply (RPS) support *	✓
Memory layout (slots x size)	1 x 32 GB	Power supply *	750 W
Storage		Number of redundant power supplies installed	1
RAID support *	✓	Operational conditions	
RAID levels	0, 1, 5, 6, 10, 50, 60	Operating temperature (T-T)	5 - 45 °C
Supported RAID controllers	940-8i 4GB	Storage temperature (T-T)	-40 - 60 °C
Graphics		Operating relative humidity (H-H)	8 - 90%
Maximum graphics card memory	16 MB	Storage relative humidity (H-H)	8 - 90%
Network		Operating altitude	0 - 3050 m
LAN controller	Broadcom 57416	Logistics data	
Ethernet LAN	✓	Harmonized System (HS) code	84714100
Cabling technology	10/100/1000Base-T(X)	Weight & dimensions	
Ethernet interface type	10 Gigabit Ethernet	Width	175 mm
Ports & interfaces		Depth	734 mm
Ethernet LAN (RJ-45) ports *	3	Height	462 mm
USB 2.0 ports quantity	1	Design	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	5	Chassis type *	Tower (4U)
VGA (D-Sub) ports quantity	1		
Serial ports quantity	1		



5415247295211

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-FEB-2025. Prints or copies of Information are only valid on the printed Publication date