# TP-Link Tapo C420S2 Polttimo IP-turvakamera Sisätila ja ulkotila 2560 x 1440 pikseliä Seinä

Tuotemerkki : TP-Link   **Tuoteperhe:** Tapo   **Tuotekoodi:** TAPO C420S2

Tuotteen nimi : C420S2

TP-Link Tapo C420S2. Malli: IP-turvakamera, Tuettu sijoitus: Sisätila ja ulkotila, Yhteysteknologia: Langaton. Kiinnitystyyppi: Seinä, Tuotteen väri: Valkoinen, Kotelo: Polttimo. Näkökentän kulma: 113°. Optisen sensorin koko: 25,4 / 3 mm (1 / 3"). Polttovälialue: 3.18 mm

Performance

Type *	IP security camera
Placement supported *	Indoor & outdoor
Connectivity technology *	Wireless
People counting function	✔

Design

Form factor *	Bulb
Mounting type *	Wall
Product colour *	White
LED indicators	System
Protection features	Dust resistant, Water resistant
International Protection (IP) code	IP65

Camera

Field of view (FOV) angle	113°

Image sensor

Optical sensor size	25.4 / 3 mm (1 / 3")
Progressive scan	✔

Lens system

Focal length range	3.18 mm

Night vision

Night vision *	✔
Night vision distance	850 m
LED type	IR

Video

Maximum resolution *	2560 x 1440 pixels
Video formats supported	H.264
Supported video modes	1440p
Frame rate	20 fps
Video streaming	✔

Audio

Built-in speaker(s)	✔
Audio system	2-way
Built-in microphone	✔

Network

Ethernet LAN *	✘
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Wi-Fi *	✔
Bluetooth *	✘

Network

Frequency band	2.4 GHz

Storage

Card reader integrated	✔
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB

Ports & interfaces

DC-in jack	✔

Security

Security algorithms	WPA, WPA2-PSK
Alert notification type	Snapshot alert message
Intelligent Video Surveillance (IVS) system features	Human detection, People counting, Vehicle detection
Motion sensor	✔

Management features

Reset button	✔

Power

Power source type *	Battery, USB
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
DC output current	3 A
Battery life	0.5 year(s)

Operational conditions

Operating temperature (T-T)	-20 - 45 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	110.6 mm
Depth	64.2 mm
Height	64.2 mm

Packaging content

Number of cameras *	2
Cables included	LAN (RJ-45), USB
Mounting kit	✔
Mounting brackets included	✔
Screws included	✔
Quick start guide	✔
USB charger included	✔

4897098688052

4897098688113

0840030708053

840030708053