

QNAP TS-464U-RP NAS Teline (1U) Intel® Celeron® N5095 8 GB DDR4 0 TB QNAP Turbo System Alumiini, musta

Tuotemerkki : QNAP

Tuotekoodi: TS-464U-RP-8G



Tuotteen nimi : TS-464U-RP

QNAP TS-464U-RP. Malli: NAS. Alustatyyppi: Teline (1U). Laitteen luokka: Pienet & Keskikokoiset Yritykset. Suoritinperhe: Intel® Celeron®, Prosessorimalli: N5095, Prosessorin taajuus: 2 GHz. Sisäinen muisti: 8 GB, Sisäisen muistin tyyppi: DDR4. Asennetun muistin kokonaiskapasiteetti: 0 TB. Käyttöjärjestelmä asennettu: QNAP Turbo System



Storage		Performance	
Supported storage drive interfaces	Serial ATA II, Serial ATA III	Buzzer	✓
Storage drive sizes supported	2.5,3.5"	Multilingual support	✓
RAID support *	✓	Snapshot	✓
RAID levels	0, 6, 1, JBOD, 5, 10	Management protocols	SNMP V2, V3
Online RAID migration	✓	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SNMPv2, SNMPv3, SSH
Online RAID expansion	✓	Access Control List (ACL)	✓
RAID rebuild	✓	Reset button	✓
Hot-swap drive bays	✓	On/off switch	✓
Supported file systems	FAT32, exFAT, HFS+, NTFS, ext3, ext4	Built-in FTP server	✓
Storage drives installed *	✗	Browser supported	Apple Safari, Google Chrome, Microsoft Edge, Mozilla Firefox
Total installed storage capacity *	0 TB	System log	✓
Number of storage drives supported *	4	Hot spare	✓
Installed storage drive type *	✗	Disk scan	✓
Supported storage drive types *	HDD & SSD	S.M.A.R.T. support	✓
Disk roaming	✓	Share folder	CIFS/SMB
Processor		Software	
Processor manufacturer *	Intel	Operating system installed *	QNAP Turbo System
Processor family *	Intel® Celeron®	Operating system version	5.0.1
Processor model *	N5095	Windows operating systems supported	Windows 10, Windows 8, Windows 7, Windows 11
Processor frequency *	2 GHz	Linux operating systems supported	Ubuntu 14.04
Processor boost frequency	2.9 GHz	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Processor cores	4	Server operating systems supported	Windows Server 2019, Windows Server 2012 R2, Windows Server 2008 R2, Windows Server 2016, Windows Server 2012
Processor threads	4	Other operating systems supported	Solaris 10
CPU configuration (max)	1		
On-board graphics card model	Intel® UHD Graphics		
Memory			
Internal memory *	8 GB		
Internal memory type	DDR4		
Maximum RAM supported	16 GB		
Memory slots	2		
Memory form factor	SO-DIMM		
Flash memory	4000 MB		

Network		Power	
Ethernet LAN *	✓	Power supply location	Built-in
Ethernet LAN data rates	10,1000,2500,100 Mbit/s	Power supply unit (PSU) capacity	250 W
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T, 2500BASE-T	Number of power supply units	2
DHCP server	✓	Redundant power supply (RPS) support	✓
Jumbo frames support	✓	Power consumption (typical)	51.404 W
iSCSI support	✓	Power consumption (sleep)	37.469 W
Wake-on-LAN ready	✓	AC input voltage	100 - 240 V
Dynamic DNS (DDNS)	✓	Fan voltage	12 V
Ports & interfaces		Weight & dimensions	
USB port *	✓	Width *	430 mm
USB 2.0 ports quantity	2	Depth *	479 mm
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2	Height *	43.3 mm
HDMI ports quantity	1	Weight	8.12 kg
HDMI version	1.4b	Package weight	10.1 kg
Ethernet LAN (RJ-45) ports *	2	Packaging content	
Concurrent connections	1500	Cables included	AC, LAN (RJ-45)
PCI Express x2 (Gen 3.x) slots	1	Power cables quantity	2
Design		Number of screws	84
Chassis type *	Rack (1U)	Processor special features	
Cooling type *	Active	Enhanced Intel SpeedStep Technology	✓
Product colour	Aluminium, Black	Idle States	✓
Number of fans	2 fan(s)	Intel 64	✓
Fan diameter	4 cm	Intel Trusted Execution Technology	✗
LED indicators	HDD, Status, Power, LAN	Intel Virtualization Technology (VT-x)	✓
Performance		Intel Virtualization Technology for Directed I/O (VT-d)	✓
Type *	NAS	Intel VT-x with Extended Page Tables (EPT)	✓
Device class *	Small & Medium Business	Operational conditions	
Backup function *	✓	Operating temperature (T-T)	0 - 40 °C
Backup features	Cloud, iSCSI LUN	Operating relative humidity (H-H)	5 - 95%
		Storage temperature (T-T)	-20 - 70 °C
		Storage relative humidity (H-H)	5 - 95%
		Logistics data	
		Harmonized System (HS) code	84714100



4711103082201

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.