

## Samsung SBB-SSNV Black 4K Ultra HD 8 GB 3840 x 2160 pixels Wi-Fi

**Brand :** Samsung

**Product code:** SBB-SS08NV2XEN

**Product name :** SBB-SSNV




- Seamless UHD Content Delivery
  - Intuitive All-in-One Operations
  - Fully-Integrated Performance Management
- UHD Signage Player Box

Samsung SBB-SSNV. Product colour: Black, Video formats supported: AVC, AVS+, H.263, H.264, HEVC, MPEG1, MPEG2, MPEG4, VC-1, VP8, VP9, Image formats supported: JPEG, PNG. Processor architecture: Cortex-A72, Processor frequency: 1700 MHz. Storage media type: eMMC, Total storage capacity: 8 GB, Compatible memory cards: SD. Internal memory: 2500 MB, Internal memory type: LPDDR4. HD type: 4K Ultra HD, Maximum video resolution: 3840 x 2160 pixels

Features		Ports & interfaces	
Product colour *	Black	RS-232C	✓
Video formats supported *	AVC, AVS+, H.263, H.264, HEVC, MPEG1, MPEG2, MPEG4, VC-1, VP8, VP9	<b>Network</b>	
Image formats supported *	JPEG, PNG	Ethernet LAN *	✓
Audio formats supported	AC3	Wi-Fi *	✓
<b>Display</b>		Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Built-in display *	✗	<b>Software</b>	
<b>Processor</b>		Operating system installed	Tizen
Built-in processor	✓	Operating system version	4.0
Processor architecture	Cortex-A72	<b>Ergonomics</b>	
Processor frequency	1700 MHz	LED indicators	✓
Processor cores	4	<b>Power</b>	
<b>Storage</b>		Power consumption (typical)	21 W
Built-in storage media *	✓	<b>Weight &amp; dimensions</b>	
Storage media type *	eMMC	Width	206.4 mm
Total storage capacity *	8 GB	Depth	165.6 mm
Card reader integrated *	✓	Height	29.9 mm
Compatible memory cards	SD	Weight	600 g
<b>Memory</b>		<b>Packaging data</b>	
Internal memory	2500 MB	Package width	379 mm
Internal memory type	LPDDR4	Package depth	249 mm
<b>Video</b>		Package height	80 mm
HD type *	4K Ultra HD	Package weight	1.5 kg
Maximum video resolution	3840 x 2160 pixels	<b>Packaging content</b>	
<b>Ports &amp; interfaces</b>		Remote control included	✓
HDMI ports quantity *	1	Cables included	AC, HDMI
HDCP *	✓	AC adapter included	✓
Ethernet LAN (RJ-45) ports *	1	<b>Operational conditions</b>	
USB 2.0 ports quantity *	2	Operating temperature (T-T)	0 - 40 °C

Ports & interfaces		Operational conditions	
Headphone outputs	1	Operating relative humidity (H-H)	10 - 80%
DC-in jack	✓		



8806094402674



8592978429324

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.