



## APC Easy 3S UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 20 kVA 20000 W

**Tuotemerkki :** APC

**Tuotekoodi:** E3SUPS20KHB

**Tuotteen nimi :** Easy 3S

APC Easy 3S. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 20 kVA, Lähtöteho: 20000 W. Akkuteknologia: Sealed Lead Acid (VRLA), Akun jännite: 220 V. Kotelo: Tower, Tuotteen väri: Valkoinen, Näytön tyyppi: LED. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH. Tuotteen leveys: 380 mm, Tuotteen syvyys: 928 mm, Tuotteen korkeus: 1400 mm



Features		Design	
UPS topology *	Double-conversion (Online)	International Protection (IP) code	IP20
Output power capacity *	20 kVA	<b>Operational conditions</b>	
Output power *	20000 W	Operating temperature (T-T)	0 - 40 °C
Waveform *	Pure sine	Storage temperature (T-T)	-15 - 40 °C
Input operation voltage (min) *	304 V	Operating relative humidity (H-H)	0 - 95%
Input operation voltage (max) *	477 V	Storage relative humidity (H-H)	0 - 95%
Input frequency *	45/65 Hz	Operating altitude	0 - 999.9 m
Output operation voltage (min)	380 V	Non-operating altitude	0 - 15000 m
Output operation voltage (max)	415 V	<b>Certificates</b>	
Output frequency	50/60 Hz	Compliance certificates	RoHS
Maximum current	37 A	Certification	CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH
Number of input phases	3	<b>Packaging content</b>	
Number of output phases	3	Quick installation guide	✓
Input power factor	0.99	<b>Weight &amp; dimensions</b>	
Output voltage Total Harmonic Distortion (THD)	3%	Width	380 mm
Input current Total Harmonic Distortion (THD)	3%	Depth	928 mm
<b>Battery</b>		Height	1400 mm
Battery technology	Sealed Lead Acid (VRLA)	Weight	122 kg
Battery voltage	220 V	<b>Packaging data</b>	
Number of batteries supported	3	Package width	563 mm
<b>Design</b>			
Form factor *	Tower		

Design		Packaging data	
Product colour *	White	Package depth	1014 mm
Display type	LED	Package height	1640 mm
		Package weight	158 kg
		Logistics data	
		Harmonized System (HS) code	85078000
		Other features	
		Output voltage	400 V



0731304340782



731304340782

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.