



## APC GVSUPS10KB4HS UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 10 kVA 10000 W

**Tuotemerkki :** APC

**Tuotekoodi:** GVSUPS10KB4HS

**Tuotteen nimi :** GVSUPS10KB4HS

APC GVSUPS10KB4HS. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 10 kVA, Lähtöteho: 10000 W. Pistorasian tyypit: Hard Wire 4-wire (3PH + G), Hard Wire 5-wire (3PH + N + G). Akkuteknologia: Sealed Lead Acid (VRLA), Akun jännite: 480 V. Kotelo: Tower, Tuotteen väri: Valkoinen, Näytön tyyppi: LCD. Sertifiointi: CSA C22.2 NO. 107.3, EN/IEC 62040-1, EN/IEC 62040-2, EN/IEC 62040-3, IEC 60721-4-2 Level 2M2, UL...



Features		Battery	
UPS topology *	Double-conversion (Online)	Battery voltage	480 V
Output power capacity *	10 kVA	<b>Design</b>	
Output power *	10000 W	Form factor *	Tower
Waveform *	Sine	Product colour *	White
Input operation voltage (min) *	340 V	Display type	LCD
Input operation voltage (max) *	460 V	<b>Operational conditions</b>	
Input frequency *	40/70 Hz	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (min)	380 V	Storage temperature (T-T)	-15 - 40 °C
Output operation voltage (max)	415 V	Operating relative humidity (H-H)	0 - 95%
Output frequency	50/60 Hz	Storage relative humidity (H-H)	0 - 95%
Maximum current	18 A	Operating altitude	0 - 1000 m
Number of input phases	3	Non-operating altitude	0 - 3000 m
Number of output phases	3	<b>Certificates</b>	
Input power factor	0.99	Certification	CSA C22.2 NO. 107.3, EN/IEC 62040-1, EN/IEC 62040-2, EN/IEC 62040-3, IEC 60721-4-2 Level 2M2, UL 1778 5th edition
Crest factor	2.5:1	<b>Packaging content</b>	
ECO mode	✓	Quick installation guide	✓
Output voltage Total Harmonic Distortion (THD)	3%	<b>Weight &amp; dimensions</b>	
Input current Total Harmonic Distortion (THD)	3%	Width	521 mm
Noise level	55 dB	Depth	847 mm
Power protection features	Overload, Short circuit		
Audible alarm(s)	✓		

Ports & interfaces		Weight & dimensions	
AC outlet types	Hard Wire 4-wire (3PH + G), Hard Wire 5-wire (3PH + N + G)	Height	1485 mm
SmartSlot	✓	Weight	330 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Package width	640 mm
		Package depth	990 mm
		Package height	1680 mm
		Package weight	360 kg
		Logistics data	
		Harmonized System (HS) code	85078000



0731304406730



731304406730

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.