



BenQ LU960ST2 Lähiprojektori 5200 ANSI lumenia DLP 1080p (1920x1080) 3D

Tuotemerkki : BenQ

Tuotekoodi: 9H.JRG77.25E

Tuotteen nimi : LU960ST2

BenQ LU960ST2. Projektorin kirkkaus: 5200 ANSI lumenia, Projektioteknologia: DLP, Projektorin oletusresoluutio: 1080p (1920x1080). Valonlähteen käyttöikä: 20000 h, Valonlähteen käyttöikä (säästötila): 38000 h. Sarjaliitännän tyyppi: RS-232, HDMI-versio: 2.0a. Korkeadynaaminen teknologia-alue (HDR): High Dynamic Range 10 (HDR10), Hybrid Log-Gamma (HLG). Nimellisteho RMS: 10 W



Projector		Network	
Projector brightness *	5200 ANSI lumens	Ethernet LAN *	✓
Projection technology *	DLP	Ethernet LAN (RJ-45) ports	1
Projector native resolution *	1080p (1920x1080)	Storage	
Contrast ratio (typical) *	3000000:1	Card reader integrated *	✗
Native aspect ratio *	16:10	Features	
Number of colours	1.07 billion colours	HDCP	✓
Horizontal scan range	15 - 135 kHz	High Dynamic Range (HDR) supported	✓
Vertical scan range	23 - 120 Hz	High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10), Hybrid Log-Gamma (HLG)
Keystone correction, horizontal	-30 - 30°	Multimedia	
Keystone correction, vertical	-30 - 30°	Built-in speaker(s) *	✓
Light source		RMS rated power	10 W
Service life of light source *	20000 h	Number of built-in speakers	1
Service life of light source (economic mode)	38000 h	Design	
Lens system		Market positioning *	Home cinema
Throw ratio	.0.5	Product type *	Short throw projector
Offset	0%	Display	
Video		Built-in display *	✗
Full HD *	✓	Power	
3D *	✓	Power source *	AC
Ports & interfaces		Power consumption (typical) *	450 W
HDMI version	2.0a	Power consumption (standby) *	0.5 W
DisplayPorts quantity	1	AC input voltage	100 - 240 V
USB 2.0 ports quantity	1	AC input frequency	50 - 60 Hz
Mini-USB 2.0 ports quantity	1		
Headphone outputs	1		
Microphone in	✓		

Ports & interfaces		Operational conditions	
Serial interface type *	RS-232	Operating temperature (T-T)	0 - 40 °C
PC in (D-Sub)	✓	Weight & dimensions	
VGA (D-Sub) ports quantity *	1	Width	479.6 mm
HDMI ports quantity *	2	Depth	402 mm
3D sync port	✓	Height	182.8 mm
DC-in jack	✓	Weight *	12 kg
Packaging content			
Remote control included *	✓	Cables included	AC
Other features			
Security updates end date			31/12/2025



4718755089473



0840046048150



840046048150

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.