

## KYOCERA ECOSYS PA2100cx Väri 1200 x 1200 DPI A4

**Tuotemerkki :** KYOCERA

**Tuoteperhe:** ECOSYS

**Tuotekoodi:** 110C0C3NL0

**Tuotteen nimi :** PA2100cx

KYOCERA ECOSYS PA2100cx. Tulostustekniikka: Laser, Väri. Värikasettien määrä: 4, Suurin toimintajakso: 65000 sivua kuukaudessa. Suurin resoluutio: 1200 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 21 ppm, Kaksipuolinen tulostus. Näyttö: LCD. Verkkovalmius. Tuotteen väri: musta, Valkoinen



Printing		Network	
Duplex printing mode	Auto	Network ready	✓
Print speed (colour, normal quality, A4/US Letter)	21 ppm	Wi-Fi *	✗
Colour *	✓	Ethernet LAN *	✓
Print technology *	Laser	Cabling technology	10/100/1000Base-T(X)
Duplex printing *	✓	Ethernet LAN data rates	10,100,1000 Mbit/s
Maximum resolution *	1200 x 1200 DPI	Near Field Communication (NFC)	✗
Print speed (black, normal quality, A4/US Letter) *	21 ppm	Bluetooth	✗
Warm-up time	32 s	Mobile printing technologies	Apple AirPrint, Kyocera Mobile Print, Mopria Print Service
Time to first page (black, normal)	11 s	Performance	
Time to first page (colour, normal)	12.5 s	Internal memory *	512 MB
Print margins (top, bottom, right, left)	4.2 mm	Maximum internal memory	512 MB
Watermark printing	✓	Card reader integrated	✗
Secure printing	✓	Built-in processor	✓
N-up printing	2, 4, 6, 8, 9, 16, 25	Processor family	ARM Cortex
Booklet printing function	✗	Processor frequency	800 MHz
Economical printing	✓	Sound pressure level (printing)	48 dB
		Sound power level (standby)	30 dB
Features		Design	
Maximum duty cycle *	65000 pages per month	Market positioning *	Home & office
Recommended duty cycle	500 - 1500 pages per month	Product colour *	Black, White
Printing colours *	Black, Cyan, Magenta, Yellow	Built-in display *	✓
Number of print cartridges *	4	Display	LCD
Page description languages *	PDF, PCL 6, XPS, PostScript 3	Touchscreen	✗
Printer fonts	PCL, PostScript	Display number of lines	2 lines
Country of origin	China	Control type	Buttons
		Certification	GS, TUV

Features		Certificates	
Replacement cartridges	TK-5430K Zwart (toner 1.250)	Waste Electrical and Electronic Equipment (WEEE) compliance	✓
	ISO/IEC 19798 TK-5430Y Geel (toner 1.250) ISO/IEC 19798 TK-5430M Magenta (toner 1.250) ISO/IEC 19798 TK-5430C Cyaan (toner 1.250) ISO/IEC 19798 TK-5440K Zwart (toner 2.800) ISO/IEC 19798 TK-5440Y Geel (toner 2.400) ISO/IEC 19798 TK-5440M Magenta (toner 2.400) ISO/IEC 19798 TK-5440C Cyaan (toner 2.400) ISO/IEC 19798		
Input & output capacity		Power	
Total number of input trays *	2	Power consumption (printing) *	345 W
Total input capacity *	300 sheets	Power consumption (ready)	33 W
Total output capacity *	150 sheets	Power consumption (PowerSave)	0.9 W
Paper tray 1 input capacity	250 sheets	Power consumption (off)	0.2 W
Multi-Purpose tray	✓	Energy Star Typical Electricity Consumption (TEC)	0.691 kWh/week
Multi-Purpose tray input capacity	50 sheets	AC input voltage	220 - 240 V
Maximum number of input trays	3	AC input frequency	50 - 60 Hz
Maximum input capacity	550 sheets	System requirements	
Maximum output capacity	150 sheets	Windows operating systems supported	✓
Paper handling		Mac operating systems supported	✓
Maximum ISO A-series paper size *	A4	Linux operating systems supported	✓
Maximum print size	216 x 356 mm	Weight & dimensions	
Paper tray media types *	Plain paper	Width	410 mm
Multi-purpose tray media types	Plain paper	Depth	410 mm
ISO A-series sizes (A0...A9) *	A4, A5, A6	Height	329 mm
ISO B-series sizes (B0...B9)	B5, B6	Weight	26 kg
Non-ISO print media sizes	Legal, Letter	Packaging data	
Custom media width	70 - 216 mm	Package width	592 mm
Custom media length	148 - 356 mm	Package depth	567 mm
Paper tray media weight	60 - 163 g/m <sup>2</sup>	Package height	460 mm
Multi-Purpose Tray media weight	60 - 220 g/m <sup>2</sup>	Package weight	27 kg
Duplex media weight	60 - 120 g/m <sup>2</sup>	Packaging content	
Ports & interfaces		Cartridge(s) included	✓
Standard interfaces	Ethernet, USB 2.0	Included cartridge capacity (black)	1500 pages
Direct printing *	✓	Included cartridge capacity (CMY)	1500 pages
USB port *	✓	Cables included	AC
USB 2.0 ports quantity	1	Logistics data	
USB connector	USB Type-A	Harmonized System (HS) code	84433210
		Technical details	
		Compliance certificates	CE



0632983074930



632983074930



0632983074923



632983074923

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.