

KYOCERA ECOSYS PA4500x 1200 x 1200 DPI A4

Tuotemerkki : KYOCERA

Tuoteperhe: ECOSYS

Tuotekoodi: 110C0Y3NLO

Tuotteen nimi : PA4500x

KYOCERA ECOSYS PA4500x. Tulostustekniikka: Laser. Värikasettien määrä: 1, Suurin toimintajakso: 150000 sivua kuukaudessa. Suurin resoluutio: 1200 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaali-laatu, A4/US Letter): 45 ppm, Kaksipuolinen tulostus. Näyttö: LCD. Verkkovalmius. Tuotteen väri: Valkoinen



Printing		Network	
Duplex printing mode	Auto	Cabling technology	10/100/1000Base-T(X)
Print resolution black	1200 x 1200 DPI	Ethernet LAN data rates	10,100,1000 Mbit/s
Colour *	✗	Near Field Communication (NFC)	✗
Print technology *	Laser	Bluetooth	✗
Duplex printing *	✓	Security algorithms	HTTPS, IPPS, IPSec, SNMPv3
Maximum resolution *	1200 x 1200 DPI	Mobile printing technologies	Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service
Print speed (black, normal quality, A4/US Letter) *	45 ppm		
Duplex print speed (black, normal quality, A4/US Letter)	22.5 ppm	Performance	
Warm-up time	16 s	Internal memory *	512 MB
Time to first page (black, normal)	5.3 s	Maximum internal memory	2500 MB
Features		Compatible memory cards	SD, SDHC
Maximum duty cycle *	150000 pages per month	Built-in processor	✓
Recommended duty cycle	5000 - 20000 pages per month	Processor family	ARM Cortex
Printing colours *	Black	Processor model	Cortex-A53
Number of print cartridges *	1	Processor frequency	1400 MHz
Page description languages *	Epson LQ, IBM ProPrinter, JPEG, OpenXPS, PCL 5e, PCL 6, PCL XL, PCLm, PDF, PWG, PostScript 3, TIFF, URF, XPS	Processor cores	2
Printer fonts	Barcode, Bitmap, PCL	Sound pressure level (printing)	54 dB
Number of printer fonts	93	Sound power level (standby)	30 dB
Replacement cartridges	TK-3400	Design	
Input & output capacity		Market positioning *	Business
Total number of input trays *	1	Product colour *	White
Total input capacity *	500 sheets	Built-in display *	✓
Total output capacity *	250 sheets	Display	LCD
Paper tray 1 input capacity	500 sheets	Colour display	✗
Paper input type	Cassette, Paper tray	Touchscreen	✗
Multi-Purpose tray	✓	Display number of lines	5 lines
Multi-Purpose tray input capacity	100 sheets	Control type	Buttons
Maximum number of input trays	5	Certification	GS, TÜV, CE
Maximum input capacity	2600 sheets	Power	
Paper handling		Power consumption (printing) *	605.5 W
Maximum ISO A-series paper size *	A4	Power consumption (standby)	8.4 W
Maximum print size	216 x 356 mm	Power consumption (PowerSave)	0.5 W
Paper tray media types *	Plain paper	AC input voltage	220 - 240 V
Multi-purpose tray media types	Legal, Letter	AC input frequency	50 - 60 Hz
ISO A-series sizes (A0...A9) *	A4, A5	System requirements	
ISO B-series sizes (B0...B9)	B5	Windows operating systems supported	✓
Non-ISO print media sizes	Legal, Letter		

Paper handling		System requirements	
Custom media width	140 - 216 mm	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Custom media length	210 - 356 mm		
Paper tray media weight	60 - 120 g/m ²		
Multi-Purpose Tray media weight	60 - 220 g/m ²		
Duplex media weight	60 - 120 g/m ²		
Ports & interfaces		Linux operating systems supported	✓
Standard interfaces	RJ-45, USB 2.0	Other operating systems supported	ChromeOS
Direct printing *	✓	Sustainability	
USB port *	✓	Sustainability certificates	Blue Angel, ENERGY STAR
USB 2.0 ports quantity	2	Weight & dimensions	
USB connector	USB Type-A / USB Type-B	Width	390 mm
Optional connectivity	Ethernet, Parallel, Wireless LAN	Depth	416 mm
Network		Height	308 mm
Network ready	✓	Weight	14.6 kg
Wi-Fi *	✗	Packaging data	
Ethernet LAN *	✓	Package width	549 mm
		Package depth	494 mm
		Package height	420 mm
		Package weight	18.5 kg
		Packaging content	
		Cartridge(s) included	✓
		Included cartridge capacity (black)	6000 pages
		Cables included	AC



0632983080030



632983080030

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.