QNAP TS-464 NAS Tower Intel® Celeron® N5095 8 GB DDR4 0 TB QNAP QTS musta

Tuotemerkki : QNAP

Tuotekoodi: TS-464-8G

Tuotteen nimi : TS-464

QNAP TS-464. Malli: NAS. Alustatyyppi: Tower. Laitteen luokka: Pienet & Keskikokoiset Yritykset. Suoritinperhe: Intel® Celeron®, Prosessorimalli: N5095. Sisäinen muisti: 8 GB, Sisäisen muistin tyyppi: DDR4. Asennetun muistin kokonaiskapasiteetti: 0 TB. Käyttöjärjestelmä asennettu: QNAP QTS






Performance Storage Supported storage drive interfaces Serial ATA III Multilingual support 1 Storage drive sizes supported 2.5,3.5,M.2 Snapshot 2 Number of M.2 (M & B) slots SNMP V2/V3 Management protocols RAID support * Share folder access right **RAID** levels 0, 1, 5, 6, 10, JBOD management FIPS 140-2, HTTPS, SNMPv2, **Online RAID migration** Security algorithms SNMPv3, SSH **Online RAID expansion** 1 Access Control List (ACL) 1 RAID rebuild Reset button 1 Supported file systems FAT32, HFS+, NTFS, ext3, ext4 On/off switch 1 Storage drives installed * X Built-in FTP server 0 TB Total installed storage capacity * Apple Safari, Google Chrome, Number of storage drives supported $_{4}$ Browser supported Microsoft Edge, Mozilla Firefox System log 1 Installed storage drive type * × Hot spare 1 HDD & SSD Supported storage drive types * Disk scan Bad block scan S.M.A.R.T. support Disk roaming Share folder Processor Backup button Intel Processor manufacturer * USB copy function Processor family * Intel® Celeron® Processor model * N5095 Software 2.9 GHz Processor boost frequency QNAP QTS Operating system installed * Processor cores 4 Operating system version 5.0.1 Processor threads 4 Windows operating systems Windows 10, Windows 11, Windows CPU configuration (max) 1 supported 7. Windows 8 Number of processors supported 1 Linux operating systems supported 1 On-board graphics card model Intel[®] UHD Graphics Mac OS X 10.10 Yosemite, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Memory Sierra, Mac OS X 10.14 Mojave, Mac Mac operating systems supported Internal memory * 8 GB OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big DDR4 Internal memory type Sur, Mac OS X 12.0 Monterey 16 GB Maximum RAM supported Windows Server 2008 R2, Windows Memory slots 2 Server 2012, Windows Server 2012 Server operating systems supported R2, Windows Server 2016, Windows Memory form factor SO-DIMM Server 2019 4000 MB Flash memory

Network		Power	
Ethernet LAN * Ethernet LAN data rates DHCP server iSCSI support Wake-on-LAN ready Dynamic DNS (DDNS)	 10,100,1000,2500 Mbit/s <td>Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (sleep) AC input voltage Fan voltage</td><td>Built-in 90 W 1 40.536 W 21.618 W 100 - 240 V 12 V</td>	Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (sleep) AC input voltage Fan voltage	Built-in 90 W 1 40.536 W 21.618 W 100 - 240 V 12 V
Ports & interfaces		Weight & dimensions	
USB port * USB 2.0 ports quantity USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity HDMI ports quantity	 2 2 1 	Width * Depth * Height * Weight Package weight	170 mm 226 mm 168 mm 2.26 kg 3.6 kg
HDMI version Ethernet LAN (RJ-45) ports *	2.0 2	Packaging content	
Design	2	External power adapter	
Chassis type * Cooling type * Product colour Number of fans	Tower Active Black 1 fan(s)	Cables included Power cables quantity Quick start guide Number of screws	AC, LAN (RJ-45) 1 ✓ 24
Fan diameter	12 cm	Processor special features	
LED indicators Cable lock slot Cable lock slot type	✓ ✓ Kensington	Enhanced Intel SpeedStep Technology Idle States	1 1
Performance		Intel 64	1
Type * Device class * Backup function * Backup features Buzzer	NAS Small & Medium Business ✓ Cloud, USB drive, iSCSI LUN	Intel Trusted Execution Technology Intel Virtualization Technology (VT- x) Intel Virtualization Technology for Directed I/O (VT-d) Intel VT-x with Extended Page Tables (EPT)	× × ×
		Operational conditions	

operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	5 - 95%
Storage temperature (T-T)	-20 - 70 °C
Storage relative humidity (H-H)	5 - 95%



4711103082324

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.