Canon i-SENSYS MF272dw Laser A4 2400 x 600 DPI 29 ppm Wi-Fi

Brand : Canon

Product family: i-SENSYS

Product code: 5621C013

Product name : MF272dw

A4, Monochrome laser, Print, copy, scan, 2400 x 600 dpi, Flatbed, USB 2.0, LAN, WLAN, 9 Kg Canon i-SENSYS MF272dw. Print technology: Laser, Printing: Mono printing, Maximum resolution: 2400 x 600 DPI. Copying: Mono copying, Maximum copy resolution: 600 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Duplex functions: Copy, Print. Maximum ISO A-series paper size: A4. Wi-Fi. Product colour: Black



| Printing | | Paper handling | |
|--|--|--|---|
| Duplex printing mode | Auto | ISO B-series sizes (B0B9) | В5 |
| Print technology * Printing * | Laser Mono printing | Non-ISO print media sizes | Executive, Legal, Letter, Oficio, Statement |
| Duplex printing * | I i i i i i i i i i i i i i i i i i i | Envelopes sizes | C5, Com-10, DL, Monarch |
| Maximum resolution * | 2400 x 600 DPI | Paper tray media weight | 60 - 163 g/m² |
| Print speed (black, normal quality, A4/US Letter) * | 29 ppm | Ports & interfaces | |
| Time to first page (black, normal) | 7.5 s | USB port | 1 |
| | | USB 2.0 ports quantity | 1 |
| Copying | | Network | |
| Duplex copying * | | Wi-Fi * | 1 |
| Copying * | Mono copying | Ethernet LAN * | 1 |
| Maximum copy resolution * | 600 x 600 DPI | Cabling technology | 10/100Base-T(X) |
| Time to first copy (black, normal) Maximum number of copies | 7.6 s 999 copies | Wi-Fi standards | 802.11b, 802.11g, Wi-Fi 4 (802.11n) |
| Copier resize | 25 - 400% | | 64-bit WEP, 128-bit WEP, WPA-AES, |
| N-in-1 copy function | 1 | Security algorithms | WPA-EAP, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-EAP, WPA2-PSK, WPA2-TKIP |
| N-in-1 copy function (N=) | 2, 4 | Management protocols | SNMPv1, SNMPv3 |
| ID-card copy function | ✓ | Mobile printing technologies | Apple AirPrint |
| Scanning | | Performance | |
| Duplex scanning * | × | | 256 MB |
| Scanning * | Colour scanning | Internal memory * | |
| Optical scanning resolution * | 600 x 600 DPI | Built-in processor | |
| Scanner type * | Flatbed scanner | Processor frequency | 1200 MHz |
| Scan to | Cloud, PC | Design | |
| Image formats supported | JPEG, PNG, TIFF | Product colour * | Black |
| Document formats supported | PDF | Market positioning * | Business |
| Input colour depth | 24 bit | Built-in display * | 1 |
| Output colour depth | 24 bit | Display | LCD |
| Greyscale levels Scan drivers | 256 Thrain Wia | Power | |
| | TWAIN, WIA | Power consumption (max) | 1300 W |
| Fax | | Power consumption (printing) | 530 W |
| Faxing * | × | Power consumption (standby) | 4.8 W |
| 5 | | | |
| Features | | Power consumption (sleep) | 1 W |
| Features Recommended duty cycle | 150 - 2000 pages per month | | 1 W 0.23 kWh/week |
| Features | 150 - 2000 pages per month 20000 pages per month Copy, Print | Power consumption (sleep) Energy Star Typical Electricity | |

| Features | | System requirements | |
|---|---|---|--|
| Printing colours * Page description languages | Black UFRII | Windows operating systems supported | Windows 10, Windows 11, Windows 8.1 Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, |
| Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper handling | 1 150 sheets 50 sheets | Mac operating systems supported | |
| Maximum ISO A-series paper size * Maximum print size Paper tray media types * ISO A-series sizes (A0A9) * | A4 216 x 356 mm Bond paper, Envelopes, Heavy paper, Labels, Plain paper, Postcard, Recycled paper, Thin paper A4, A5, A6 | Linux operating systems supported Server operating systems supported | Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura Vindows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022 |
| | | Operational conditions Operating relative humidity (H-H) Operating temperature (T-T) | 20 - 80% 10 - 30 °C |
| | | Weight & dimensions Width Depth Height | 372 mm 320 mm 271 mm |

Weight

9 kg



4549292197143

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.