

## Targus AEM350 videoneuvottelujärjestelmä 8 henkilö(t) 8,5 MP Ryhmävideoneuvottelujärjestelmä

**Tuotemerkki** : Targus

**Tuotekoodi**: AEM350EUZ

**Tuotteen nimi** : AEM350

Targus AEM350. Tuotetyyppi: Ryhmävideoneuvottelujärjestelmä, Henkilöiden lukumäärä: 8 henkilö(t). Anturin tyyppi: CMOS. HD-tyyppi: 4K Ultra HD, Suurin kuvataajuus: 30 fps. Digitaalinen zoomaus: 5x. Tuotteen väri: musta



<b>Performance</b>		<b>Camera</b>	
Number of persons *	8 person(s)	Image sensor size *	1/2.8"
Number of cameras	1	Horizontal field of view	120°
Product colour *	Black	Vertical field of view	76°
Camera cable length (max)	2 m	Diagonal field of view	128°
Product type *	Group video conferencing system	Remote control interface	IR Wireless
Wall mountable	✓	Aperture range (F-F)	2.2 - 2.2
Tilt angle range	16 - 10°	Lens type	Wide-angle
Noise level	85 dB	<b>Microphone</b>	
<b>Video</b>		Microphone sensitivity	-26 dB
HD type *	4K Ultra HD	Microphone frequency	120 - 16000 Hz
Maximum video resolution *	3840 x 2160 pixels	Number of microphone arrays	6
Maximum frame rate	30 fps	<b>Features</b>	
Video codecs	MJPEG, YUY2	Maximum operating distance	6 m
<b>Audio</b>		Control method	IR remote
Built-in speaker(s)	✓	<b>Computer system</b>	
Number of speakers	2	Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows 8.1
Frequency range	200 - 16000 Hz	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Audio system full duplex	✓	<b>Power</b>	
Audio beamforming	✓	Power source type	AC
Voice codecs	AGC	<b>Weight &amp; dimensions</b>	
Noise reduction	✓	Width	35.2 mm
Echo cancellation	✓		
Automatic gain control	✓		
Microphone pick-up range	6 m		
<b>Ports &amp; interfaces</b>			
USB connector type	USB Type-B		

Ports & interfaces		Weight & dimensions	
AC (power) in	✓	Depth	11.8 mm
AUX in (speaker)	✓	Height	75.5 mm
		Weight	890 g
Camera		Packaging content	
Megapixel (approx.) *	8.5 MP	Cables included	Power, USB
Camera type	Single camera	Wall mounting kit	✓
Zoom capability	✓	AC adapter included	✓
Digital zoom	5x	Mounting kit	✓
Sensor type *	CMOS	Warranty card	✓
		Remote control included	✓
		Manual	✓
		Screws included	✓



5051794042214

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 30-DEC-2024. Prints or copies of Information are only valid on the printed Publication date