Epson Perfection V39II Tasoskanneri 4800 x 4800 DPI A4 musta

Tuotemerkki : Epson

Tuoteperhe: Perfection

Tuotekoodi: B11B268401

Tuotteen nimi : V39II

Epson Perfection V39II. Skannauksen enimmäiskoko: 216 x 297 mm, Optinen skannauserottelutarkkuus: 4800 x 4800 DPI, Tulon värisyvyys: 48 bittiä. Skannerityyppi: Tasoskanneri, Tuotteen väri: musta, Ohjaustyyppi: Painikkeet. Anturin tyyppi: CIS, Valonlähde: Valkoinen LED, Tiedostomuodot (skanneri): BMP, JPEG, PDF, TIFF. Suurin ISO A-luokan paperikoko: A4, ISO A-sarjan koot (A0...A9): A4. Virtalähteen tyyppi: USB, Virrankulutus: 2,5 W, Virrankulutus (pois päältä): 0,013 W





		-	
Scanning		Power	
Maximum scan size *	216 x 297 mm	Power supply type *	USB
Optical scanning resolution *	4800 x 4800 DPI	Power consumption (typical)	2.5 W
Colour scanning	J	Power consumption (off)	0.013 W
Duplex scanning *	×	Weight & dimensions	
Input colour depth	48 bit	Width	249 mm
Output colour depth	24 bit	Depth	364 mm
Movement resolution	4800 DPI	Height	39 mm
Design		Weight	1.5 kg
Scanner type *	Flatbed scanner	Packaging data	
Product colour *	Black	Quantity per pack	1 pc(s)
Control type	Buttons	Packaging content	
Built-in display *	×	Cables included	USB
Performance		System requirements	
Sensor type *	CIS	System requirements	Windows 10 Windows 7 Windows
Light source Scan file formats	White LED BMP, JPEG, PDF, TIFF	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows XP
Button functions	Copy, On, Scan to PDF		Mac OS X 10.6 Snow Leopard, Mac
Scan drivers	ICA, TWAIN	Mag apparating systems supported	OS X 10.7 Lion, Mac OS X 10.7.5
Paper handling		Mac operating systems supported	Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Maximum ISO A-series paper size *	A4	Operational conditions	
ISO A-series sizes (A0A9)	Α4	• Operating temperature (T-T)	10 - 35 °C
Letter	1	Storage temperature (T-T)	-20 - 60 °C
Legal	1	Operating relative humidity (H-H)	20 - 80%
Ports & interfaces		Storage relative humidity (H-H)	20 - 80%
USB port *	1	Logistics data	
USB port *	2.0	Country of origin	Indonesia
	2.0	country of origin	indeficitu



8715946715308

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.