



## APC SRTL1000RM4UXLI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 1 kVA 900 W 8 AC-pistorasia(a)

**Tuotemerkki :** APC

**Tuotekoodi:** SRTL1000RM4UXLI

**Tuotteen nimi :** SRTL1000RM4UXLI



APC SRTL1000RM4UXLI. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 900 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Litiumioni (Li-Ion), Akun kapasiteetti: 2400 ah, Akun jännite: 48 V. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Hopea, Telineen kapasiteetti: 4U. Vaatimustenmukaisuustodistukset: CE, RoHS, Sertifiointi: RoHS, CE



Features		Battery	
UPS topology *	Double-conversion (Online)	Battery life (max)	10 year(s)
Output power capacity *	1 kVA	<b>Design</b>	
Output power *	900 W	Form factor *	Rackmount/Tower
Waveform *	Sine	Rack capacity	4U
Input operation voltage (min) *	160 V	Cable length	1.83 m
Input operation voltage (max) *	275 V	Modular	✓
Input frequency *	40/70 Hz	Product colour *	Black, Silver
Output operation voltage (min)	220 V	Control type	Buttons
Output operation voltage (max)	230 V	Display type	LCD
Output frequency	50/60 Hz	International Protection (IP) code	IP20
Surge energy rating	340 J	<b>Operational conditions</b>	
Crest factor	3:1	Operating temperature (T-T)	0 - 40 °C
Emergency Power Off (EPO)	✓	Storage temperature (T-T)	-15 - 45 °C
Noise level	50 dB	Operating relative humidity (H-H)	0 - 95%
Power source type	AC	Storage relative humidity (H-H)	0 - 95%
Detachable power cord	✓	Operating altitude	0 - 3048 m
<b>Ports &amp; interfaces</b>		Non-operating altitude	0 - 15240 m
AC outlet types	C13 coupler	<b>Certificates</b>	
Power plug	C14 coupler	Compliance certificates	CE, RoHS
AC outlets quantity	8 AC outlet(s)	Certification	RoHS, CE
<b>Battery</b>		<b>Packaging content</b>	
Battery technology	Lithium-Ion (Li-Ion)	Rack mount kit	✓
Battery capacity	2400 Ah	<b>Sustainability</b>	
Battery voltage	48 V	Sustainability certificates	Green Premium
Typical backup time at full load	136 min	<b>Weight &amp; dimensions</b>	
Typical backup time at half load	252 min	Width	432 mm

**Weight & dimensions**

Depth	59 mm
Height	171 mm
Weight	40.7 kg



0731304508939



731304508939



8592978510732

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.