## QNAP

## QNAP QSW-IM1200-8C verkkokytkin Hallittu L2 musta

Tuotemerkki : QNAP Tuotekoodi: QSW-IM1200-8C

Tuotteen nimi: QSW-IM1200-8C



QNAP QSW-IM1200-8C. Kytkin tyyppi: Hallittu, Kytkinkerros: L2. Console-portti: RS-232. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 240 Gbit/s. Verkkostandardit: IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE.... DC-syöttöjännite: 9 - 54 V. Telineasennus



| Management features                         |   | Design                            |                                      |
|---|---|-----------------------------------|--------------------------------------|
| Switch type *                               | Managed   | Product colour                    | Black                                |
| Switch layer                                | L2  | Reset button                      | ✓                                    |
| Quality of Service (QoS) support            | <b>✓</b>  | LED indicators                    | Activity, Link, Power, Speed, Status |
| Web-based management                        | ✓   | Electromagnetic compatibility     | CLASS A                              |
| Ports & interfaces                          |   | Performance                       |                                      |
| Basic switching RJ-45 Ethernet ports type * | ×   | Firmware upgradeable              | ✓                                    |
|   |   | Fanless                           | ✓                                    |
| Gigabit Ethernet (copper) ports quantity    | 1   | Power                             |                                      |
| Combo SFP ports quantity                    | 8   | Power source *                    | DC                                   |
| SFP+ module slots quantity                  | 4   | Power supply included *           | ✓                                    |
| Console port                                | RS-232  | DC input voltage                  | 9 - 54 V                             |
| Network                                     |   | Power consumption (max)           | 78 W                                 |
| Networking standards *                      | IEEE 802.1Q, IEEE 802.1ab, IEEE<br>802.1p, IEEE 802.1w, IEEE 802.3,<br>IEEE 802.3ab, IEEE 802.3ad, IEEE<br>802.3ae, IEEE 802.3an, IEEE<br>802.3az, IEEE 802.3bz, IEEE 802.3u,<br>IEEE 802.3x, IEEE 802.3z | Power over Ethernet (PoE)         |                                      |
|   |   | Power over Ethernet (PoE) *       | ×                                    |
|   |   | Operational conditions            |                                      |
|   |   | Operating temperature (T-T)       | -30 - 65 °C                          |
| 10G support *                               | ✓   | Operating relative humidity (H-H) | 5 - 95%                              |
| Copper ethernet cabling technology          | 10GBASE-T, 100BASE-T, 1000BASE-<br>LX, 1000BASE-SX, 1000BASE-T,   | Weight & dimensions               |                                      |
|   | 2500BASE-T  | Width                             | 285 mm                               |
| Full duplex                                 | <b>✓</b>  | Depth                             | 238 mm                               |
| Flow control support                        | ✓   | Height                            | 43.5 mm                              |
| Auto-negotiation                            | ✓   | Weight                            | 4.58 kg                              |
| VLAN support                                | ✓   | Packaging content                 |                                      |
| Data transmission                           |   | Cables included                   | AC                                   |
| Switching capacity *                        | 240 Gbit/s  | Quick start guide                 | <b>✓</b>                             |
| Throughput                                  | 120 Gbit/s  | Packaging data                    |                                      |
| MAC address table *                         | 16000 entries   | Rack rails                        | 1                                    |
| Jumbo frames support                        | ✓   | Package weight                    | 5.31 kg                              |
| Jumbo frames                                | 9000  | Certificates                      | -                                    |
| Security                                    |   | Certification                     | CE, FCC, VCCI, BSMI                  |
| DHCP features                               | DHCP client   |                                   | . , , ,                              |

| Security                  |   | Logistics data                       |
|---------------------------|---|--------------------------------------|
| Access Control List (ACL) | ✓ | Harmonized System (HS) code 85176990 |
| IGMP snooping             | ✓ |                                      |
| Design                    |   |                                      |
| Rack mounting *           | ✓ |                                      |



4713213519042

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.