## Allied Telesis AT-GS980EM/11PT-50 Hallittu L3 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki 1U Harmaa



Tuotemerkki : Allied Telesis

Tuotekoodi: 990-006932-50

Tuotteen nimi : AT-GS980EM/11PT-50

Allied Telesis AT-GS980EM/11PT-50. Kytkin tyyppi: Hallittu, Kytkinkerros: L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 8. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 24 Gbit/s. Verkkostandardit: IEEE 802.1AX, IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE.... Power over Ethernet -tuki. Telineasennus, Kotelo: 1U

Management features		Design	
Switch type *	Managed	Rack mounting *	1
Switch layer	L3	Stackable *	×
Quality of Service (QoS) support		Form factor	10
Web-based management	1	Product colour	Grey
System event log	1	LED indicators	
Ports & interfaces		Electromagnetic compatibility	EN55032 A, FCC A, VCCI A, ICES-003 A
Basic switching RJ-45 Ethernet ports quantity *	8	Performance	
Basic switching RJ-45 Ethernet ports	Gigabit Ethernet (10/100/1000)	Memory type	DDR3-SDRAM
type * Fiber ports quantity	2	Internal memory	512 MB
Fiber optic connector	SFP	Flash memory	128 MB
Network		Export Control Classification Number (ECCN)	5A992C
Network	IEEE 802.1AX, IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s,	Power	
		Power supply included *	1
	IEEE 802.1v, IEEE 802.1w, IEEE 802.1x, IEEE 802.2, IEEE 802.3, IEEE	Power consumption (max)	98 W
Networking standards *	802.3ab, IEEE 802.3ac, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	1
		Power over Ethernet (PoE) pass through	1
10G support *	×	Power over Ethernet plus (PoE+)	8
Port mirroring		ports quantity	5
Full duplex		Operational conditions	
Flow control support		Operating temperature (T-T)	0 - 50 °C
Link aggregation	1	Storage temperature (T-T)	-25 - 70 °C
Spanning tree protocol	1	Operating relative humidity (H-H)	5 - 90%
Auto-negotiation		Storage relative humidity (H-H)	5 - 95% 0 - 3000 m
VLAN support	1	Operating altitude Heat dissipation	75 BTU/h
Virtual LAN features	Private VLAN, Voice VLAN		15 510,11
Number of VLANs	4094	Weight & dimensions	210
Data transmission		Width Depth	210 mm 180 mm
Switching capacity *	24 Gbit/s	Height	42.5 mm
Forwarding rate	16.4 Mpps	Weight	1.6 kg
MAC address table *	16000 entries		1.0 Kg
Number of queues	8	Packaging data	417
Jumbo frames support	10000	Package width	417 mm
Jumbo frames	10000 1.5 MP	Package depth Package height	336 mm 151 mm
Packet buffer memory	1.5 MB	Package neight	3.5 kg
Security			···y
DHCP features	DHCP snooping		
Access Control List (ACL)	1		

Security		Certificates	
Security algorithms	3DES, 128-bit AES, 192-bit AES, 256-bit AES, AES, DES, MD5, PEAP, SHA-1, SHA-2, SHA-256, SSH, SSL/TLS, TLS, TTLS	Certification	EN55024, EN61000-3 UL60950-1, CAN/CSA-C22.2 No. 60950-1-03, EN60950-1, EN60825-1, AS/NZS 60950.1 UL, CUL ROHS
BPDU filtering/protection	✓	Logistics data	
Authentication	MAC-based authentication, Web- based authentication	Harmonized System (HS) code	8517.62.0050
Multicast features			
Multicast support	✓		
Protocols			
GARP VLAN Registration Protocol (GVRP)	1		
Routing protocols	OSPF, RIP, RIP-2		





767035217789

0767035217789

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.