## Allied Telesis AT-x550-18XSPQm-50 Hallittu 10G Ethernet (100/1000/10000) Power over Ethernet -tuki Hopea

Tuotemerkki : Allied Telesis

Tuotekoodi: 990-005107-50

Tuotteen nimi : AT-x550-18XSPQm-50

Allied Telesis AT-x550-18XSPQm-50. Kytkin tyyppi: Hallittu. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: 10G Ethernet (100/1000/10000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 8. Kytkevien optisten moduulien tyyppi: 40 Gigabit Ethernet. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 480 Gbit/s. Verkkostandardit: IEEE 1588, IEEE 802.1AX, IEEE 802.1D, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE 802.1x, IEEE.... Power over Ethernet -tuki

Management features		Performance	
Switch type *	Managed	Memory type	DDR-SDRAM
Ports & interfaces		Internal memory	1024 MB
Basic switching RJ-45 Ethernet ports quantity *	8	Flash memory Noise level	1024 MB 47 dB
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Export Control Classification Number (ECCN)	5A992A
SFP+ module slots quantity	8	Power	
QSFP+ module slots quantity	4	Power consumption (typical)	99 W
Network		Power consumption (max)	391 W
80 IE 80 Networking standards * IE 80 80 80 80 80 80 80 80 80 80	IEEE 1588, IEEE 802.1AX, IEEE 802.1D, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE 802.1x, IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3an, IEEE 802.3at, IEEE 802.3az, IEEE 802.3ba, IEEE 802.3bz, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	1
		Power over Ethernet plus (PoE+) ports quantity	8
		Power over Ethernet (PoE) power per port	30 W
		Total Power over Ethernet (PoE) budget	240 W
Port mirroring		Operational conditions	
IP routing		Operating temperature (T-T)	0 - 45 °C
Link aggregation		Storage temperature (T-T)	-25 - 70 °C
VLAN support		Operating relative humidity (H-H)	5 - 90%
Number of VLANs	4094	Storage relative humidity (H-H)	5 - 95%
Optical fiber		Operating altitude Heat dissipation	0 - 3048 m 1334 BTU/h
Switching optical modules type	40 Gigabit Ethernet		1554 010/11
		Weight & dimensions	110
Data transmission	400 01:14	Width	440 mm 260 mm
Switching capacity *	480 Gbit/s	Depth Height	44 mm
Forwarding rate MAC address table *	357.1 Mpps 16000 entries	Weight	44 mm 4.2 kg
Latency (10-100 Mbps)	2.3 µs		T.2 Kg
Latency (1 Gbps)	3.8 μs	Certificates	DellC
Latency (10 Gbps)	3 μs	Certification	RoHS
Number of queues	8	Logistics data	
Jumbo frames support	1	Harmonized System (HS) code	85176990
Packet buffer memory	4 MB		
Security			
DHCP features	DHCP client		
BPDU filtering/protection	1		
Design			
Stackable *	1		
Product colour	Silver		
Safety	UL, cUL, TUV		





767035210216

0767035210216

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.