

Delock WLAN WiFi 6 Antenna RP-SMA plug 4 - 6 dBi directional with magnetic base with tilt joint

Description

This Wireless LAN antenna by Delock can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals. With the help of the variable inclination of the antenna tilt and the magnetic base, the antenna can be positioned individually.



Specification

- Connector: 1 x RP-SMA plug
- With tilting joint, rotatable
- Frequency range:
2.400 - 2.500 GHz
5.150 - 5.875 GHz
- Antenna gain:
4 dBi @ 2.5 GHz
6 dBi @ 5.7 GHz
- Impedance: 50 Ohm
- VSWR: 2.0
- Polarisation: linear, vertical
- HBW horizontal beamwidth: 80°
- VBW vertical beamwidth: 70°
- Operating temperature: -10 °C ~ 55 °C
- Housing material: ABS UV resistant
- Cable type: RG-174
- Cable colour: black
- Cable length: ca. 1 m
- Dimensions (LxWxH): ca. 115.5 x 90.0 x 80.0 mm

System requirements

- Device with a free RP-SMA jack

Package content

- WLAN antenna

Item no. 90297

EAN: 4043619902972

Country of origin: Taiwan, Republic of China

Package: • White Box

Images

