



## D-Link AX3600 19216 Mbit/s Valkoinen Power over Ethernet -tuki

**Tuotemerkki** : D-Link

**Tuotekoodi**: DWL-X8630AP

**Tuotteen nimi** : AX3600

D-Link AX3600. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 19216 Mbit/s. Tietoturva-algoritmit: AES, TKIP. Ethernet LAN -datanopeudet: 10,100,1000,2500 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen. Tehonkulutus (maks.): 19,98 W



Features		Ports & interfaces	
2.4 GHz *	✓	Ethernet LAN (RJ-45) ports *	2
5 GHz *	✓	<b>Power</b>	
Maximum data transfer rate *	19216 Mbit/s	Power over Ethernet (PoE) *	✓
Maximum data transfer rate (2.4 GHz)	9176 Mbit/s	Power consumption (max)	19.98 W
Maximum data transfer rate (5 GHz)	19216 Mbit/s	<b>Design</b>	
Ethernet LAN data rates	10,100,1000,2500 Mbit/s	Product colour *	White
Frequency band	2.4 - 5 GHz	Housing material	Plastic
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1Q, IEEE 802.3at	<b>Antenna</b>	
Channels quantity	165 channels	Antenna type *	Internal
Automatic channel selection	✓	Antenna direction type	Omni-directional
MIMO	✓	Antenna gain level (max)	4 dBi
MIMO type	Multi User MIMO	<b>Certificates</b>	
Wi-Fi Multimedia (WMM)/(WME)	✓	Certification	CE, EN55032, EN55024, EN61000-3-2, EN61000-3-3, EN60601- 1-2 (Medical electrical equipment), EN301489-1, EN301489-17, EN300328, EN301893 FCC, IC cUL+UL (UL/CSA 62368-1 + UL 60950-22) LVD (IEC/EN 62368-1) CB (IEC/EN 60950-1 + 62368-1) RCM NCC BSMI (CNS 14336-1) UL2043
VLAN support	✓	<b>Weight &amp; dimensions</b>	
Band steering	✓	Width	220 mm
Quality of Service (QoS) support	✓	Depth	220 mm
Mean time between failures (MTBF)	485222 h	Height	47 mm
<b>Security</b>		Weight	868 g
Security algorithms *	AES, TKIP	<b>Operational conditions</b>	
MAC address filtering	✓	Operating relative humidity (H-H)	10 - 90%
Service Set Identifier (SSID) features	Multiple SSIDs	Operating temperature (T-T)	0 - 40 °C
Number of SSID supported	32	Storage temperature (T-T)	-20 - 65 °C
<b>Protocols</b>		Storage relative humidity (H-H)	5 - 95%
Management protocols	SNMP v1/v2c/v3, Telnet, SSH	<b>Logistics data</b>	
<b>Management features</b>		Harmonized System (HS) code	85176990
Web-based management	✓		
Command-line interface (CLI)	✓		



0790069452918



790069452918

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.