StarTech.com

StarTech.com MST30C2HHPDU kannettavien tietokoneiden telakka ja porttitoistin Langallinen USB 3.2 Gen 1 (3.1 Gen 1) Type-C musta, Hopea

Tuotemerkki : StarTech.com   **Tuotekoodi:** MST30C2HHPDU

Tuotteen nimi : MST30C2HHPDU

StarTech.com MST30C2HHPDU. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery asti: 60 W. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. Tuotteen väri: musta, Hopea, Tiedonsiirtonopeus: 5 Gbit/s, Digitaalinen enimmäistarkkuus: 4096 x 2160 pikseliä. Virtalähteen malli: AC, AC-syöttöjännite: 100 - 240 V, Syöttöjännite: 1.5 A. Windows-käyttöjärjestelmätuki: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10...

Dual Monitor USB-C Dock

Ports & interfaces		Power	
Connectivity technology *	Wired	Compatible power plug types	EU, UK
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C	**Software**	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4	Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1		
USB Power Delivery (USB PD)	✔		
USB Power Delivery revision	2.0		
USB Power Delivery up to	60 W		
HDMI ports quantity *	2		
Combo headphone/mic port	✔		
Headphone outputs *	1		
Headphone connectivity	3.5 mm		
Network			
Ethernet LAN *	✔		
Ethernet LAN (RJ-45) ports	1		
Ethernet LAN data rates	10,100,1000 Mbit/s		
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u		
Auto MDI/MDI-X	✔		
Full duplex	✔		
Performance		**Operational conditions**	
Card reader integrated *	✘	Operating temperature (T-T)	5 - 35 °C
Data transfer rate	5 Gbit/s	Storage temperature (T-T)	-40 - 70 °C
Maximum digital resolution	4096 x 2160 pixels	Operating relative humidity (H-H)	5 - 95%
Product colour *	Black, Silver	**Sustainability**	
Plug and Play	✔	Sustainability compliance	✔
UASP support	✔		

Performance

Housing material	Plastic

Power

Power source type	AC
AC input voltage	100 - 240 V
Input current	1.5 A
Output voltage	20 V
Output current	4.5 A
Power consumption (typical)	100 W
Power plug type	Type N

Weight & dimensions

Width	80 mm
Depth	220 mm
Height	24 mm
Weight	259 g

Packaging data

Package width	157 mm
Package depth	267 mm
Package height	90 mm
Package weight	1.5 kg

Packaging content

Cables included	USB Type-C
AC adapter included	✔
Quick start guide	✔

Technical details

Compliance certificates	CE, RoHS

Logistics data

Products per master (outer) case	6 pc(s)
Master (outer) case width	287 mm
Master (outer) case length	337 mm
Master (outer) case height	304 mm
Harmonized System (HS) code	84733020

Other features

Chipset	VIA/VLI - VL813, MegaChips - STDP4320, Realtek - RTL8153, C-Media - CM6533, Texas Instruments - TPS65983

0065030872690

065030872690