Shuttle

Shuttle XPC nano NS02EV2 Rockchip RK3368 2 GB DDR3L-SDRAM 16 GB eMMC Android 8.1 Mini-PC Mini PC musta

Tuotemerkki : Shuttle   **Tuoteperhe:** XPC nano   **Tuotekoodi:** PFB-NS02E041

Tuotteen nimi : NS02EV2

Shuttle XPC nano NS02EV2. Suoritinperhe: Rockchip, Prosessorimalli: RK3368. Sisäinen muisti: 2 GB, Sisäisen muistin tyyppi: DDR3L-SDRAM. Kokonaistallennuskapasiteetti: 16 GB, Tallennusmedia: eMMC, Integroitu kortinlukija. Sisältyvän näytönohjaimen malli: PowerVR SGX6110. Wi-Fi. Käyttöjärjestelmä asennettu: Android 8.1. Virtalähde: 24 W. Alustatyyppi: Mini-PC. Tuotetyyppi: Mini PC. Paino: 270 g. Tuotteen väri: musta

Processor

Processor manufacturer *	Rockchip
Processor family *	Rockchip
Processor model *	RK3368
Processor cores	8
Processor boost frequency	1.5 GHz

Memory

Internal memory *	2 GB
Maximum internal memory *	2 GB
Internal memory type	DDR3L-SDRAM

Storage

Total storage capacity *	16 GB
Storage media *	eMMC
Optical drive type *	✗
Card reader integrated	✔
Compatible memory cards	SD, SDHC, SDXC

Graphics

Discrete graphics card *	✗
On-board graphics card *	✔
Discrete graphics card model *	Not available
On-board graphics card model *	PowerVR SGX6110
Graphics card Open GL support	✔

Network

Ethernet LAN *	✔
Ethernet LAN data rates	10,100,1000 Mbit/s
Cabling technology	10/100/1000Base-T(X)
LAN controller	Realtek RTL8211F-CG
Wi-Fi *	✔
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Bluetooth	✔
Bluetooth version	5.0
Wake-on-LAN ready	✔

Ports & interfaces

USB 2.0 ports quantity *	4
HDMI ports quantity *	1
HDMI version	2.0

Ports & interfaces

DC-in jack	✔

Design

Chassis type *	Nettop
Volume	0.577 L
VESA mounting	✔
Cable lock slot	✔
Cable lock slot type	Kensington
Product colour *	Black
Housing material	Plastic

Performance

Audio chip	Realtek ALC5640-VB
Password protection	✔
Product type *	Mini PC

Software

Operating system installed *	Android 8.1

Power

Power supply *	24 W
Power supply input voltage	100 - 240 V
Power supply input frequency	50 - 60 Hz

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%

Certificates

Compliance certificates	RoHS
Certification	CE, FCC, BSMI, RCM, VCCI

Sustainability

Sustainability certificates	ErP

Weight & dimensions

Width *	141 mm
Depth *	141 mm
Height *	29 mm
Weight *	270 g
Package weight	650 g

Packaging content

Display included *	✗

Ports & interfaces		Packaging content	
Ethernet LAN (RJ-45) ports	1	VESA mount included	✔
Line-out	✔		

Logistics data	
Harmonized System (HS) code	84715000

0887993601540

887993601540