

## Chieftec Task TPS-600S virtalähdeyksikkö 600 W 20+4 pin ATX ATX musta



**Tuotemerkki :** Chieftec

**Tuoteperhe:** Task

**Tuotekoodi:** TPS-600S

**Tuotteen nimi :** TPS-600S

Chieftec Task TPS-600S. Kokonaisteho: 600 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 47 - 63 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 65 cm, SATA-virtakaapelin pituus: 150,500 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Bronze. Tuotteen väri: musta, Tuulettimen halkaisija: 12 cm, Tuulettimien määrä: 1 tuuletin(ta). Tuotteen leveys: 150 mm, Tuotteen syvyys: 140 mm, Tuotteen korkeus: 87 mm



Power		Ports & interfaces	
Total power *	600 W	PCI Express power cable length	50 cm
AC input voltage *	100 - 240 V	ATX power connector (20+4 pin)	✓
AC input frequency	47 - 63 Hz	Cabling type	Non-Modular
Input current	9 A		
Power factor	0.9	Performance	
Power Factor Correction (PFC) type	Active	80 PLUS certification *	80 PLUS Bronze
Combined power (+12V)	552 W	Supported motherboard form factors	ATX
Combined power (-12V)	3.6 W	Purpose *	PC
Combined power (+5Vsb)	12.5 W	Power supply unit (PSU) form factor *	ATX
Max output current (+3.3V)	19 A	Certification	ErP, CE, CB, EAC, TUV
Max output current (+12V)	46 A		
Max output current (+5V)	17 A	Design	
Max output current (-12V)	0.3 A	Product colour	Black
Max output current (+5Vsb)	2.5 A	Fan diameter	12 cm
Power protection features	Over voltage, Overheating, Overload, Short circuit, Under voltage	Number of fans	1 fan(s)
Ports & interfaces		Weight & dimensions	
Motherboard power connector *	20+4 pin ATX	Width	150 mm
Motherboard power cable length	65 cm	Depth	140 mm
Number of SATA power connectors	5	Height	87 mm
SATA power cable length	150,500 mm	Weight	1.67 kg
Peripheral (Molex) power connectors (4-pin) *	3	Packaging data	
Peripheral (Molex) power cable length	150,500 mm	Package weight	2.08 kg
EPS power connector (4+4 pin)	✓	Package type	Box
PCI Express power connectors (6+2 pin)	2	Technical details	
		Compliance certificates	RoHS
		Logistics data	
		Harmonized System (HS) code	84733020
		Other features	
		EPS cable length	65 cm



0753263076496



753263076496

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.