![tp-link logo]

TP-Link TL-SG116P verkkokytkin Hallitsematon Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta

Tuotemerkki : TP-Link　　　　　　　　　**Tuotekoodi:** TL-SG116P

Tuotteen nimi : TL-SG116P

TP-Link TL-SG116P. Kytkin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 16. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 32 Gbit/s. Verkkostandardit: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. DC-syöttöjännite: 9 V. Power over Ethernet -tuki. Seinäkiinnitteinen

Management features

Switch type *	Unmanaged
Quality of Service (QoS) support	✔

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity *	16
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	16

Network

Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6
Port mirroring	✔
Full duplex	✔
Flow control support	✔
Link aggregation	✔
Broadcast storm control	✔
Rate limiting	✔
Auto MDI/MDI-X	✔
Auto-negotiation	✔
Cable length detection	✔
VLAN support	✔
Virtual LAN features	Protocol-based VLAN, Tagged VLAN
Number of VLANs	32

Security

IGMP snooping	✔
Loop protection	✔

Design

Stackable *	✔
Product colour	Black
Housing material	Metal
LED indicators	✔
Wall mountable	✔

Power

Power supply included *	✔
AC input voltage	220 V
AC input frequency	50 Hz
DC input voltage	9 V
Input current	0.6 A
Power consumption (typical)	11.72 W
Power consumption (max)	144.28 W

Power over Ethernet (PoE)

Power over Ethernet (PoE) *	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	490.55 BTU/h

Weight & dimensions

Width	286 mm

Data transmission

Switching capacity *	32 Gbit/s
Forwarding rate	23.81 Mpps
MAC address table *	8000 entries
Store-and-forward	✔
Number of queues	4
Jumbo frames support	✔
Jumbo frames	9000
Packet buffer memory	4.1 MB

Weight & dimensions

Depth	111.7 mm
Height	25.4 mm

Packaging content

Quick start guide	✔

Packaging data

Package width	227 mm
Package depth	434 mm
Package height	70 mm
Package weight	2 kg

4895252500318

0840030708398

840030708398

4895252500301