

StarTech.com TB3DKM2DPL kannettavien tietokoneiden telakka ja porttitoistin Langallinen Thunderbolt 3 Harmaa

Tuotemerkki : StarTech.com

Tuotekoodi: TB3DKM2DPL

Tuotteen nimi : TB3DKM2DPL

StarTech.com TB3DKM2DPL. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: Thunderbolt 3. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u. Tuotteen väri: Harmaa, Tiedonsiirtonopeus: 5 Gbit/s, Digitaalinen enimmäistarkkuus: 3840 x 2160 pikseliä. Windows-käyttöjärjestelmätuki: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10..., Mac-käyttöjärjestelmätuki: Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High..., Tuetut palvelinkäyttöjärjestelmät: Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 x64. Tuotteen leveys: 69 mm, Tuotteen syvyys: 124 mm, Tuotteen korkeus: 27 mm



Ports & interfaces		Operational conditions	
Connectivity technology *	Wired	Operating temperature (T-T)	5 - 40 °C
Host interface *	Thunderbolt 3	Storage temperature (T-T)	-20 - 70 °C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	1	Operating relative humidity (H-H)	0 - 95%
DisplayPorts quantity	2	Weight & dimensions	
Microphone in *	✗	Width	69 mm
Network		Depth	124 mm
Ethernet LAN *	✓	Height	27 mm
Ethernet LAN (RJ-45) ports	1	Weight	147.8 g
Ethernet LAN data rates	10,100,1000 Mbit/s	Packaging data	
Wake-on-LAN ready	✓	Package width	139 mm
Networking standards	IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u	Package depth	195 mm
		Package height	37 mm
		Package weight	270 g
Performance		Packaging content	
Card reader integrated *	✗	Manual	✓
Data transfer rate	5 Gbit/s	Technical details	
Maximum digital resolution	3840 x 2160 pixels	Compliance certificates	CE, RoHS
Number of displays supported	2	Logistics data	
Product colour *	Grey	Products per master (outer) case	24 pc(s)
Housing material	Aluminium, Plastic	Master (outer) case width	300 mm
		Master (outer) case length	437 mm
		Master (outer) case height	270 mm
		Harmonized System (HS) code	84733020
		Other features	
		Cable length	0.28 m

Software	Other features
Windows operating systems supported	Chipset Intel JHL6540 (Alpine Ridge), Texas Instruments TPS65983A, Parade PS176, ASMedia ASM1042A, Intel WGI210
Mac operating systems supported	
Server operating systems supported	



0065030888059



065030888059

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.